

Monarch by Falcon - Exits

19 Series - Vertical Rod Device



Manufactured to the same exacting standards as the 19 Rim, the 19-V Exit Device complies with most exit door requirements, and is fully reversible and surface applied. This device is regularly furnished with deadlocking top latch with latch retention and square bolt at bottom.







Latch retention hold is in the top latch. Retainer is released when it engages the strike.



Features:

- Part number 19VEO X Finish
- Function Stocked: Exit only
- Trims Separately: Note: Lever trim is handed See Trim page
 - 1906T Thumb piece (new number 910)
 - 1909NL Night latch (new number 910NL)
 - 1910L Entry Lever Dane (new number 912L)
 - 914KIL BE Key in Lever(sectional) Blank Escutcheon
 - 914KIL IC Key in Lever (sectional) Lever Entry X IC core
 - 914KIL KD Key in Lever (sectional) Lever Entry
- 914KIL NL Key in Lever (sectional) Lever Night Latch
- Finishes: Aluminum and Duro
- Lengths: 36" X 84" and 48" X 84"
- ANSI A156.3 2001 Grade 1 Standard; UL Listed



2130

F19 Series - Fire Rated **Vertical Rod Device**



3788 Strike Manufactured to the same exacting standards as the F-19 Rim, the F-19-V Fire Exit Device complies with most exit door requirements, and is fully reversible and surface applied. This device is regularly furnished with deadlocking top latch retention and square bolt at bottom. (This device is listed by UL for B label fire door installations.)





Latch retention hold is in the top latch. Retainer is released when it engages the strike. The door is in the closed position.



Features

- Part number F19VE X Finish
- Function Stocked: "EO" exit only
- Trims Separately: Note: Lever trim is handed See trim page
- 1906T Thumb piece (new number 910)
- 1909NL Night latch (new number 910NL)
- 1910L Entry Lever Dane (new number 912L)
- 914KIL BE Key in Lever(sectional) Blank Escutcheon
- 914KIL IC Key in Lever (sectional) Lever Entry XIC core
- 914KIL KD Key in Lever (sectional) Lever Entry
- 914KIL NL Key in Lever (sectional) Lever Night Latch
- Finishes Aluminum and Duro
- Lengths: 36" X 84' and 48" X 84"
- ANSI A156.3 Grade 1 standard
- UL "B" labeled 1-1/2 hour door



2130