

Falcon - Exits

25 R Series - Rim Exit Device



299 Strike



2789
Dogging Key



Cylinder Dogging

Features

- Non handed
- 299 strike standard, other strikes available on special order
- Latch bolt: Stainless Steel, 3/4" throw
- Dogging Feature: 1/2 turn hex dogging standard, No thread parts to wear out
- Stock sizes: 36" and 48" width doors,
- ANSI: Certified ANSI A156.3-2001 Grade 1
- Sex Bolts: (optional) Recommended when device is used with hollow core wood, composite or light gauge hollow metal doors, For EO device specify eight (8) #2729 sex bolts. With Trim specify four (4) 2729 sex bolts
- EL function : Can be interfaced with Building security systems.

Options:

Cylinder Dogging kit: Specify 25CDK
1-1/8" Mortise cylinder not included.

Stocked Product

36" door width US3, US26, 313AN, US26D
48" door width 313AN, US26D

EL Function stocked: 36" door width 26D

F25-R Series - Fire Rim Exit Device



299F Strike



Features

- Non Handed
- "A" label 3 hours 4' 0" X 8' 0"; 8' 0" X 8'0" with F4023 Mullion
- "B" label 1-1/2" hour for 8'0" X 8') with KRF4023 Mullion
- 299F strike standard, other strikes available on special order
- Latch bolt: stainless Steel, 3/4 " throw
- Deadlocking latch bolt standard
- Stock sizes: 36" and 48" width doors
- Mounting Height: 40-1/4" form CL to finished floor
- Fasteners: All mounting screws are concealed, All machine screws standard
- Sex Bolts: (optional) Required when device is used with hollow core wood, composite or light gauge hollow metal doors, For EO device specify eight (8) #2729 sex bolts. With Trim specify four (4) 2729 sex bolts
- ANSI: Certified ANSI A156.3 2001 Grade 1 Standards

- EL function : Can be interfaced with Building security systems.

Stocked Product

36" door width US3, US26, 313AN, US26D
48" door width :313AN, 26D

EL Function stocked : 36" door width, 26D