

## Falcon - Exits

### 25 V Series - Vertical Rod Exit Device

#### Features:

- Hand: Field Reversible
- Strikes: 3788 Top strike is surface applied; 2130 bottom strike is mortised into the floor
- Latch bolt: Top stainless steel  $\frac{3}{4}$  throw; Bottom bolt is  $\frac{1}{2}$ " throw
- Latch Retention Hold: Standards with top latch
- Sex Bolts: ( Optional) Recommended when device is used with hollow core wood, composite or light gauge hollow metal doors, For EO device, specify twelve (12) #2729 sex bolts,, For devices with trim specify eight (8) #2729 sex bolts'
- ANSI : Certified ANSI A156.3-2001 Grade 1 standard
- EL function : Can be interfaced with Building security systems.

#### Options:

Cylinder Dogging kit: Specify 25CDK  
1-1/8" Mortise cylinders not included.  
12" & 36" Extension rods Available.

#### Stocked Product

36" X 96" door size US3, US26, 313AN, US26D  
48" X 96" door size 313AN, US26D

EL function stocked: 36" X 96" door size 26D



### F25 V Series - Fire Vertical Rod Device

#### Features

- Hand: Field Reversible
- UL: "A" Label 3 hour; 8' X 10' 90 minute same egress, 8' X 10'
- Wood Door: 20 minute 8' X 10'; 90 minute 8' X 9'
- Strikes: 3788 Top strike is surface applied; 2130 bottom strike is mortised into the floor
- Latch bolt: Top stainless steel  $\frac{3}{4}$  throw; Bottom bolt is  $\frac{1}{2}$ " throw
- Deadlocking Latch bolt: Standard in top latch
- Latch Retention Hold: standard with top latch
- F25-V LBR; Less bottom rod vertical device; "A" Label 3 hour- 8' X 8' 90 minute same egress' Wood Door 20 minute 8' X 8' openings. (F-LBR Must be ordered in pairs)
- Fasteners: All mounting screws area concealed machine screws
- Sex Bolts: ( Optional) Required when device is used with hollow core wood, composite or light gauge hollow metal doors, Fro EO device, specify twelve (12) #2729 sex bolts,, For deices with rim specify eight (8) #2729 sex bolts'
- ANSI: Certified ANSI A156.3 Grade 1 standard
- EL function : Can be interfaced with Building security systems.

#### Options:

12" & 36" Extension rods Available.

#### Stocked Product

F25 V Stock Finishes: 36" X 96" 313AN, US26D  
48" X 96" 313 AN, US26D

F25 V LBR Stocked : 36" X 96" and 48" X 96" 313AN,US26D  
(Must be ordered in pairs)

EL Function stocked: 36" X 96" 26D