

Falcon

19, 25, and XX Accessories and Options

Removable Mullion



- The F4023, KRF-4023 and KR-4023 steel mullions are for use with the 19-R, 25-R, and XX-R devices on double door openings. Advantage: Increased security and tighter closure. Minimizes door warpage and sag. Regulates the flow of in-and-out traffic.
- Falcon removable mullions are easily removed and reinstalled for full width access.
- Rim devices are used on both leaves, attaining a perfectly symmetrical opening.
- The mullion assembly consists of a mullion, top and bottom mounting brackets and a screw pack.
- The F4023 and KRF-4023 fire-rated mullions also include four stabilizer blocks as required for labeled installations.
- Mullions may be cut on the job for doors under stock lengths.
- KR Mullions require 1 1/4" mortise cylinder with standard A cam.

Features


- Mullion fittings – ductile iron.
- F4023, 4023, KRF-4023 and KR-4023– 2" x 3" x height.
- 2923 mullion - 1-1/2' x 2-1/2' x height.
- Prime coat only.
- 7' or 8' door opening standard, other door opening as specified.

Cylinders

- Cylinder supplied only when specified.
- Cylinders keyed different unless specified keyed alike.

Sex Bolts

- 325 (1/4"-20 Thread)
- 425 (#10-24 Thread)



DOUBLE DOOR APPLICATION

Strike	Installed With	Min. Stile	B *
299	2923 mullion	4 1/8"	3"
299	4023 mullion	4 3/8"	3 1/4"
299-F	F-4023 mullion	4 3/8"	3 1/4"
499-F	F-4023 mullion	4 1/2"	3 5/16"
264	2923 mullion	4"	2 7/8"
264	4023 mullion	4 1/4"	3 1/8"
1439	2923 mullion	3 7/8"	2 3/4"
1439	4023 mullion	4 1/8"	3"
1606	2923 mullion	4 1/4"	2 5/8"
1606	4023 mullion	4 1/2"	2 7/8"
1609	Surface 25-V	4"	2 3/8"

*Backset to vertical center line on the device.

Stocked Product

4023,F4023 7'2" & 8'0" Prime Coat
 KR4023,KRF4023 7'2" & 8'0" Prime Coat