

## Adams Rite - Store Front Hardware Accessories

### 4016 - Header Bolt for Aluminum Stile Doors

#### Product Description & Features

- **Strike:** For header bolt a 1/2" diameter hole in metal frame is suitable, or for non metal installations, 4005 strike is available
- **Adjustment:** Exact adjustment of threaded rod to cylinder height is locked in place by hexagonal threshold bolt.
- **Door/Cylinder Height:** The standard version is designed for a 7' door height with cylinder height as low as 35". Can also be ordered for up to 10' door with additional extension.
- **Function:** Adding the 4016 Header Bolt and the 4015 Threshold Bolt to a pivoted MS® deadbolt allows for Maximum Security for pairs of doors by the turn of a single key. Simultaneously extending the stainless steel hexbolts top and bottom and pivoting the massive MS® deadbolt into the mating stile, the three-point lock secures the entire double door entrance. The 4016 can be added to any basic MS1850S, MS1850SN or for two-points top and bottom use with 1870/1870HM Cylinder-Operated Flushbolt. Not applicable to 7/8" backset locks.
- **Header Bolt:** Hexagonal 3/8" flat to flat. Made of stainless steel.
- **Threshold Bolt:** Hexagonal 3/8" flat to flat. Made of stainless steel.
- **Operation:** 360° turn of key or thumbturn in basic MS lock throws counterbalanced bolt into opposite door and hexagonal bolt into header strike.
- **Options:** For "universal" application, specify 4015-18 with fully threaded rod for cut off to any cylinder height below 53".

#### Stocked Product:

| Item#     | Backset |
|-----------|---------|
| 4016-2001 | 31/32"  |
| 4016-3001 | 1-1/8"  |

