

Hager

1756 - 200 Degree Door Viewer

Features:

- Requires 9/16" (14 mm) hole for viewer
- For doors 1-3/8" (35 mm) to 2-1/8" (54 mm) thick, adjustable
- Tamper resistant
- 90 minute fire rated
- One way viewer
- Brass
- Meets ANSI A156.16 for L03221



Stocked Product

Finishes:

US3, US10A, US15, US15A, US26

232W - Convex Wall Stop

Features:

- Meets ANSI A156.16 for L02101
- Diameter: 2-7/16" (62 mm)
- Projection: 1" (25 mm)
- Wrought brass, bronze, stainless steel with grey rubber bumper
- Fasteners: One (1) #10 x 1-1/2" PPHWS with plastic and toggle anchor

Notes:

- Specify 232T for machine screw and toggle nut screw pack (10 pk)
- BL232W is 232W case quantity 50
- Concealed tamper proof mounting
- Easy installation by inserting screwdriver through small hole in bumper



Stocked Product

Finishes:

US3, US10B, US26, US32D

236W - Concave Wall Stop

Features:

- Meets ANSI A156.16 for L02101
- Diameter: 2-7/16" (75 mm)
- Projection: 1" (25 mm)
- Wrought brass, bronze, stainless steel with grey rubber bumper
- Fasteners: One (1) #10 x 1-1/2" PPHWS with plastic and toggle anchor for drywall

Notes:

- Specify 230T for machine screw and toggle nut screw pack (10 pk) for concrete
- BL236W is 236W case quantity 50
- Easy installation by inserting screwdriver through small hole in bumper
- Concave rubber bumper prevents damage to locksets with projecting buttons
- Concealed tamper proof mounting



Stocked Product

Finishes:

US3, US10B, US26, US32D