

# HES

## Electric Strike

### 8000 - Series

This field selectable fail safe/fail secure unit requires no cutout on the frame for fast, easy installation. It accommodates 1/2-5/8" latchbolts (with 1/8" door gap). With patented vertical adjustability to accommodate door sag or misalignment, the 5900 sets the standard for concealed electric strikes.



#### Specifications

- ANSI/BHMA 156.31, Grade 1
- UL Pending
- Patented design

#### Electrical

- .24 Amps @12VDC
- .12 Amps @ 24VDC
- DC Continuous Duty/AC Intermittent Duty

#### Standard Features

- No cutting on frame required
- Vertical adjustability to accommodate door sag
- Tamper resistant

#### Stocked Product

Item	Finish
8000	630
Faceplate Options:	
801 - 4-7/8" x 1-1/4" square corner	
Finish: 613, 630	

(NOTE: Shown with optional 801 Faceplate)

### 9500 - Series (Fire Rated)

9500 series is the fire rated version of the 9600 series. Designed for use with 3' or 4' exit devices



#### Specifications:

- NFPA 252, ASTM E152
- UL 10C fire rated, 90 minutes (fail secure only)
- UL305
- Warnock Hersey UBC 7-297, UBC 7-294
- Electrical .45 Amps @ 12VDC  
.25 Amps @ 24VDC
- ANSI / BHMA 156.31 Grade 1
- NFPA Specification 252

#### Features of both:

- Dual voltage 12/24 VDC
- Heavy duty designed for 3' or 4' exit device
- Field selectable fail secure / fail safe
- Tamper resistant - heavy duty
- Completely surface mounted
- Non handed
- Horizontal lockdown screws
- Accommodates up to a 3/4" throw pullman latch
- 5 year warranty

### 9600 - Series (Non Fire Rated)

Designed for use with 3' or 4' exit devices



#### Specifications:

- UL1034 burglary-resistant rated
- ANSI/BHMA, 156.31 Grade 1 (#E09731, #E09732)
- Patented Design



#### Stocked Product

Item	Finish
9500	630
9600	613, 630