

Rockwood

555 - Lever Extension Flush Bolt

Brass.

Features:

- For Fire Rated Hollow Metal Swinging Doors measuring up to 4'w x 10'h rated up to and including 3 Hours.
- Fits ANSI A115 door and frame preparation.
- 3/4" bolt throw, 3/4" rod backset.
- 12" rod length (center of face to bolt end - retracted).
- 1 1/2" adjustable bolt head.
- Exterior pack screw packs, stainless steel plated to match – use EXP suffix (481H x EXP) when ordering.



Stocked Product

No.	Size	Finish
555	Face plate: 1" x 6-3/4" Strike: 15/16" x 2-1/4" Guide: 1" x 2"	605, 613, 625, 626

557 - Lever Extension Flush Bolt

Cast brass.

Features:

- For Fire Rated Plastic & Wood Covered Doors measuring up to 4'w x 10'h rated up to and including 1-1/2 Hours.
- 3/4" bolt throw, 3/4" backset; door strength maintained by corner reinforcing plate.

Options:

Use No. 570 Dust Proof Strike to prevent dirt blocking bottom strike.



Stocked Product

No.	Size	Finish
557	Face plate: 1" x 6-3/4" Strike: 15/16" x 2-1/4"	605, 613, 625, 626