

Schlage - *F Locks*

F Functions – ANSI A156.2, Series 4000, Grade 2

- Radius and circular face plates for F10/F40 functions
- Radius, square, and circular face plates for F51, F358 function
- 6 pin solid brass cylinder, keyed 5 pin
- Universal backset either 2-3/8" or 2-3/4"
- 1-3/8" - 1-3/4" thick door



F60

Entrance Lock

Deadbolt thrown or retracted by key from outside or by inside turn unit. Latch retracted by thumbpiece from outside or by inside knob/lever.

Consists of:

F58 Outside trim

F59 Inside trim



F93

Dummy Trim

Outside and Inside Dummy Trim
For use as door pull or as dummy trim on inactive leaf of pair of doors. Fixed thumbpiece and inside knob/lever. Dummy cylinder with inside plate.

Consists of:

F92 Outside trim

F94 Inside trim



F10 ANSI F75

Passage Latch

Both knobs/levers always unlocked.



F170

Single Dummy Trim

Dummy trim for one side of door.
Used for door pull or as matching inactive trim.



F40 ANSI F76

Bath/Bedroom

Privacy Lock

Push-button locking. Can be opened from outside with small circular tool. Turning inside knob/lever releases button.



F51 ANSI F81

Entrance Lock

Unlocked by key from outside when outer knob is locked by turn-button in inside knob. Inside knob/lever always unlocked.