

Schlage - S200 Locks

S 200 Locks - ANSI A156.12, 1992, Grade 2



S210D ANSI F95

Entrance, Single Locking
Deadbolt operated by key from
outside or by turn unit from inside.
Bolt automatically deadlocks when
fully thrown. Latch retracted by
lever from either side. Turning inside
lever retracts deadbolt and latch
simultaneously for immediate exit.







S251PD ANSI F97

Entrance, Double Locking
Deadbolt operated by key from

outside or by turn unit from inside.
Bolt automatically deadlocks when fully thrown. Outside lever unlocked by key from outside when locked by turn button in inside lever. Turning inside lever retracts deadbolt and latch simultaneously for immediate exit. Latch automatically deadlocks when door is closed.



S251 SAT



Standard Features:

All S200 stocked standard.

2-3/4" backset, optional 2-3/8" backset available.

UL Listed for 3 hour fire door.

Strike 1-1/8" x 2-1/4" square corner faceplate/T Strike

Door Range 1-3/8" - 2" thickness

Keyway Classic "C", Everest available upon request

Center to Center 4" CTC

Stocked Product

FUNCTION S210 S251	DESIGN Neptune Saturn Neptune Saturn	FINISHES 626 613,626 613,626
	Outum	010,020

Standard Deadlatch

16-228 2-3/8" or 2-3/4" BS



Stocked Parts 613,626 finishes

16-228 Dead Latch, Square Corner, 2-3/8"-2-3/4"BS, 1-1/8" X 2-1/4" Face Plate, 1" hsg