

Command Access Technologies

Electrified Mortise Lock

ML9080EU Modified Schlage Chassis 24 VAC/DC - Fail Secure

ML9080EL Modified Schlage Chassis 24 VAC/DC - Fail Safe

Features:

- 12V and 24V Models Available
- Current Draw: 12V – 600 MA, 24V – 300 MA
- Built in Rectifier for AC or DC operation
- Optional REX (request to exit) switch available
- 3 Year warranty

Stocked Product:

- ML9080 EU 24V
- ML9080 EL 12V and 24V
- ML9080 EU 24V with REX switch



Electrified Cylindrical Locks

ND80PEU Modified Schlage ND Lock - 24 VAC/DC - Fail Secure

ND80PEL Modified Schlage ND Lock - 24 VAC/DC - Fail Safe

Features:

- 24V Models
- Current draw 12V – 600 MA, 24V – 300 MA
- Optional REX (request to exit available/special order)
- 3 Year warranty

Options / Special Orders

- Sparta Design
- REX Switch

Stocked Product

- Finishes 613, 625, 626
- Design Schlage Rhodes
- ND80 12V EL (fail safe)
- ND80 24V EU (fail secure)
- ND80 24V EL (fail safe)



Notes:

- Available in all Schlage Designs and Finishes
- Current Draw 300mA @ 24V