

ASSEMBLY AND INSTALLATION INSTRUCTIONS

PD30148 / PD30157 / PD30159 / PD30144 / PD30142 / PD30146 / PD30151 / PD30153

WARNING: BE SURE TO SHUT OFF POWER AT THE MAIN FUSE OR CIRCUIT BREAKER BOX BEFORE INSTALLING OR SERVICING THIS FIXTURE.

NOTE: 1. Before installing, consult local electrical codes for wiring requirements.
2. Please read the instructions carefully before you install this fixture. If you are not familiar with installations, please consult the qualified electrician.

1. Thread the cord through the canopy and strain relief. Measure the desired length of the cord (A) from the canopy to the glass and leave an additional 9" of cord (B) above the canopy (include the canopy). Then cut off the unnecessary cord. (See Fig.1)
2. Adjust strain relief a 9" position from the top of the cord.
3. Mark the 3" of cord (C) from the top of the cord (B). Use a knife to peel off the insulation of the cord (C) carefully to expose the 3 wires on the inside. (See Fig.1)
Caution: Cutting too deep may cut off the three inside wires and destroy the insulation surface of the three inside wires.
4. Peel off the 3 wires from the top about 3/8" long(D) to expose the copper for wiring.
5. Unscrew the screws and washers from the mounting strap.
6. Mount mounting strap securely to ceiling box with 2 mounting screws through the slot in the mounting strap.
7. Pull out the outlet wires and the house grounding wire from the outlet box. Make wire connections using the wire nuts:
 - The clear wire with black line and marked "L" from the fixture to the black wire from the power source.
 - The clear wire marked "N" from the fixture to the white wire from the power source.
 - The clear grounding wire with green line and marked "GND" from the fixture to the green grounding wire from power source.Carefully tuck wires back into the outlet box.
8. Pull the cord (A) down slightly until the Strain Relief touches the hex nut. Attach the canopy to the mounting strap by using 2 screws.
Note: Adjusting the strain relief can decrease or increase the length of cord that is exposed.
9. Install a bulb (not included). See relamping label at socket area or packaging for maximum allowed wattage.
10. Turn on the power at the main fuse or circuit breaker box.

