

Issuing Date 01-July-2015



Revision Number

SAFETY DATA SHEET

Revision Date



The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is @ 2014 UL LLC. All rights reserved.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE **COMPANY/UNDERTAKING**

Product identifier

Product Name Prolong Transmission Treatment

PSL15000, PSL15220, PSL15225, PSL15020 Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Transmission Treatment

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier Name GoldenWest Lubricants, Inc. **Supplier Address** 1937 Mount Vernon Avenue

Pomona, CA 91768-3312

US

Supplier Phone Number Phone:909-865-3081

Fax:909-865-4467

Supplier Email info@gwlinc.com

Emergency telephone number

Chem-Trec(US & Canada) Phone: 800-424-9300

Chem-Trec (International) Phone: 703-527-3887 (Collect)





2. HAZARDS IDENTIFICATION		
Classification Not classified		

GHS Label elements, including precautionary statements

Emergency Overview

Signal word:

Hazard Statement:

Warning

Maybe harmful if swallowed and enters airways

Irritant May cause harm to breast-fed children. Harmful to aquatic life.

Reproductive toxicity Combustible liquid.



Appearance Clear, light orange

Physical State Oil Viscous liquid

Odor Hydrocarbons Oily

Precautionary Statements - Prevention

Obtain special instructions before use. Do not breathe mist or vapor. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment.

Precautionary Statements - Response

If in eyes: Rinse cautiously with water for several minutes. Remove Contact Lenses, if present and easy to do. Continue rinsing. If eye irritation persists get medical attention. Persons with preexisting skin or respiratory disorders may have their conditions aggravated by overexposure to this material.

Precautionary Statements - Storage

Store away from incompatible materials.

Precautionary Statements - Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified (HNOC)

None known.

Unknown Toxicity

Unknown % of the mixture consists of ingredient(s) of unknown toxicity.

Other information

Harmful to aquatic life with long lasting effects.

Interactions with Other Chemicals

No information available.







Product is a mixture.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%	Trade Secret
Alkanes, C14-16, Chloro	63449-39-8	15-20	*
Distillates, Petroleum, Hydrotreated Light	64742-53-6	40-60	*
Solvent Naphtha (Petroleum), Heavy Arom.	64742-94-5	2-5	*
Butylbenzene, tert-	98-06-6	1-2	*
Mineral Oil	64742-53-6	1-3	*
Mineral Oil	Not determined	1-3	*
Naphthalene	91-20-3	<0.3	
Benzene, 1,2,3,5-tetramethyl-	527-53-7	<.06	

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

First aid measures

General Advice

Note: When using this product in high pressure equipment - Accidental high velocity dermal injection of this material requires immediate medical attention.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention immediately if symptoms occur.

Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Inhalation

Remove to fresh air. Get medical attention immediately if symptoms occur.

Ingestion

Call a physician or poison control center immediately. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed

Most Important Symptoms and Effects

No information available.

Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Treat symptomatically. Keep victim under observations. Symptoms may be delayed.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

CAUTION: Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical





Page 3/11

No information available.

Uniform Fire Code Combustible Liquid: III-B

Hazardous Combustion Products

Normal combustion forms carbon dioxide and water vapor, and may produce oxides of carbon, sulfur hydrogen chloride and nitrogen. Incomplete combustion can produce carbon monoxide.

Explosion Data

Sensitivity to Mechanical Impact No.

Sensitivity to Static Discharge No.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For Personal protection, see section 8 of the SDS.

Other Information

Refer to protective measures listed in Sections 7 and 8.

Environmental Precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

Methods and material for containment and cleaning up

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Never return spills to original containers for re-use. For disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe mist or vapor. Provide adequate ventilation. Should be handled in closed systems, if possible. Pregnant or breastfeeding women must not handle this product. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Keep out of the reach of children. Store away from incompatible materials (see Section 10 of the SDS).

Incompatible Products Oxidizing agent.





8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Petroleum distillates, Hydrotreated	TWA: 5 mg/m ³ , as oil mist,	TWA: 5 mg/m ³ , as oil mist,	
Light	mineral	mineral	
64742-53-6			
Mineral Oil	TWA: 5 mg/m3		
64742-53-6	Threshold Limit Values (03		
	2014)		
Solvent naphtha (petroleum) heavy	TWA: 200 mg/m3 (as total	TWA: 500 ppm 2,000 mg/m3	
aromatic	hydrocarbon vapor)	(OSHA Z-1)	
64742-94-5			

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir. 1992) See section 15 for national exposure control parameters.

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/Face Protection

Tight sealing safety goggles.

Skin and Body Protection

Wear protective gloves and protective clothing.

Respiratory Protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

Hygiene Measures

When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Thermal Hazards

Wear appropriate thermal protective clothing, when necessary.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical and Chemical Properties

Physical State Oil, Viscous liquid, Liquid

Appearance Oily Liquid





Color Orange

Odor Hydrocarbons Oily
Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks Method</u>

Ha Unknown None known Melting / freezing point No data available None known Boiling point / boiling range No data available None known Flash Point >275°F (Typical) None known **Evaporation Rate** No data available None known No data available None known

Flammability (solid, gas) Flammability Limit in Air

Upper flammability limit
Lower flammability limit
No data available
No data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone known

Specific Gravity(H²O=1): 1.0

Water SolubilityInsoluble in waterNone knownViscosity (cPs):39.0@ 40°C(Typical)None knownExplosive propertiesNo data available

Oxidizing Properties

Oensity (g/mll):

No data available
No data available
8.24 (Typical)

Other Information

Softening Point No data available VOC Content g/l) No data available

10. STABILITY AND REACTIVITY

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing. Vapors may form explosive mixture with air.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Keep away from open flames, hot surfaces and sources of ignition.

Incompatible materials

Halogens and halogenated compounds. Strong oxidizing agents.

Hazardous Decomposition Products

May cause dense smoke, oxides of carbon, hydrogen chloride, nitrogen, sulfur, and calcium.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information





Inhalation High concentrations may cause headache, dizziness, drowsiness.

Eye Contact Irritating to skin.

Skin Contact Can be irritating or drying to skin.

Ingestion Headache, dizziness, drowsiness are possible; not a typical route of industrial exposure.

Component Information Specific test data for the substance or mixture is not available.

Information on toxicological effects

Symptoms No information available.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

The classification pertaining to the chlorinated paraffin is applicable to commercial chlorinated paraffin of average carbon chain-lengths of C12. The chlorinated paraffin present in this product is a chlorinated paraffin of a longer carbon chain-length, which is considered an IARC Class 3 for carcinogenicity (limited evidence). Petroleum products are known to cause cancer because of carcinogenic components (e.g. benzene). These carcinogenic components may be removed during the refinement process. The

classification pertaining to the chlorinated paraffin is applicable to commercial chlorinated paraffin's of average carbon chain-lengths of C12. The chlorinated paraffin present in this product is a chlorinated paraffin of a longer carbon chain-length, which is considered an

IARC Class 3 for carcinogenicity (limited evidence).

Chemical Name	ACGIH	IARC	NTP	OSHA
Petroleum distillates, Hydrotreated Light				
64742-53-6				
Alkanes, C14-16, Chloro 63449-39-8				
98-06-6Butylbenzene,				
tert-				
98-06-6				
Mineral Oil				
64742-53-6				
Mineral Oil Not Determined				

ACGIH (American Conference of Governmental Industrial Hygienists)

This product is not listed as carcinogenic.

IARC (International Agency for Research on Cancer)

The International Agency for research on cancer had concluded that highly or severely refined light and middle distillates are Group 3 substances, "not classifiable as to their carcinogenicity to humans," based on inadequate.

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

This product is not listed as carcinogenic.







Reproductive Toxicity May cause harm to breastfed babies.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Chronic Toxicity Avoid repeated exposure. Prolonged exposure may cause chronic effects.

Target Organ Effects Respiratory system. Eyes. Skin. Gastrointestinal tract (GI).

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document Not applicable ATE mix (oral)

1,135,135.00

12. ECOLOGICAL INFORMATION

Eco toxicity

Harmful to aquatic life with long lasting effects.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Mineral Oil	EC50 (Green algae (Scenedesmus quadricauda), 3 days):>100 mg/l	96h LC50: > 100 mg/l (Fathead Minnow, 4d))		24h EC50: = >10,000 mg/l
Petroleum distillates, hydro treated heavy paraffinic 64742-54-7		96h LC50: > 5000 mg/l (Oncorhynchus mykiss)		48h EC50: > 1000 mg/l
Solvent naphtha (petroleum) heavy aromatic 64742-94-5		96h LL50 (Oncorhynchus mykiss (rainbow troup)): 2 mg/l		48h EL50: 1.4 mg/l
Butylbenzene, tert- 98-06-6		48h LC0 44 mg/l Leuciscus idus 48h LC50 65 mg/l Leuciscus idus (Golden orfe		24h LC50 41 mg/l
Alkanes, C14-16, Chloro 63449*-39-8		96h LC50 0.06-0.08 mg/l Rainbow trout, Donaldson trout (Oncorhynchus mykiss) 96h LC50 >10,000 mg/l Bleak (Auburnus alburnus) 96h L50 10.7 mg/l Bluegill (Lepomis macrochurus		





Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Solvent naphtha (petroleum) heavy aromatic 64742-94-5upplier Trade Secret	3.2-4.5
Mineral Oil	No data available

Other adverse effects

No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Disposal methods This material, as supplied, is not a hazardous waste according to Federal regulations (40

CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether the altered material is a hazardous waste. Consult the appropriate state, regional, or local

regulations for additional requirements.

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

14. TRANSPORT INFORMATION

DOT Not Regulated

TDG Not Regulated

IMDG

UN number UN3082

UN proper shipping name Environmentally hazardous substances, liquid, n.o.s.(Alkanes, C14-17, chloro)

Transport hazard class(es)

Class 9
Subsidiary risk Label(s) 9
Packing group III

Environmental hazards

Marine pollutant Yes

EmS Not available

<u>IATA</u> Not regulated

ADN Not regulated





15. REGULATORY INFORMATION

International Inventories

TSCA Complies.

DSL/NDSL All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory.

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List.

US Federal Regulations

This product is considered a "Hazardous Chemical" as defined by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200).

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product may a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Acute Health HazardYesChronic Health HazardYesFire HazardNoSudden release of pressure hazardNoReactive HazardNo

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material.

US State Regulations

OSHA Specifically Regulated Substances(29 CFR 1910.1001-1050)

Not Listed.

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Naphthalene	<0.3% in product
Toluene	<.06% in product
Sulfur dioxide	<29.00 PPM
Trimethyl phosphate	<5.00 PPM
Benzene	<3.00 PPM
Ethyl benzene	<10.00 PPM
Naphthalene	<10.00 PPM

U.S. State Right-to-Know Regulations

International Regulations

Mexico

National occupational exposure limits





Page 10/11

16. OTHER INFORMATION

NFPA Health Hazards 1 Flammability 1 Instability 0 Physical and Chemical

Hazards -

HMIS Health Hazards 1* Flammability 1 Physical Hazard 0 Personal Protection B

Chronic Hazard Star Legend * = Chronic Health Hazard

Prepared By

Issuing Date 01-July-2015

Revision Date

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet







Page 11 / 11