



@geekvape

@geekvapeftech



MADE IN CHINA

REGIS KIT

User Manual 4.5ML

OVERVIEW



English 102

Product Specifications

Product Parameters

Product Name: Aegis kit
Maximum power output: 100W
Output mode: Adjustable
Material: Aluminum + zinc alloy + silicone
Dimensions: 37.8*46.80*135mm
Battery: 18650 / 26650 / 20700 / 21700
(Battery not included)

Battery low voltage warning: 3.3V ± 0.1V
PCBA temperature safety shutoff: 75 °C
Maximum firing duration: 10 seconds
Maximum Voltage output: 9V ± 0.1V
Operating temperature: -40 °C ~ +80 °C

Resistance range

Mode	Min	max
1 POWER	0.05	3
2 NI200	0.05	0.8
3 TI	0.05	1.1
4 SS316	0.05	1.65
5 BYPASS	0.05	3

Contents

- 1* Aegis mod
- 1* Shield sub ohm tank (0.4ohm)
- 1* 0.15 ohm coil head
- 1* Spare silica glass
- 1* 20700/21700 battery cap
- 1* 18650 battery adapter
- 1* Silicone seal replacement
- 2* Spare Torx Screws
- 1* User Manual

English 103

How to use

Instructions

- Turn On:** Press the FIRE button 5 times in quick succession to turn on the device.
- Turn Off:** Press the FIRE button 5 times in quick succession to turn off the device.
- Setting state:** Press the FIRE button 3 times in quick succession to enter the Setting state.
- Switch between working modes:** (POWER/TC-NI/TC-SS/TC-TI/TC-TCR/VRC/BYPASS) In the setting state use the (+) & (-) button to toggle between modes, press and hold the FIRE button for 0.8s or allow 5s of inactivity to select.
- TCR Set up:** On the mode selection screen toggle to TC-TCR, press and hold the fire button to enter the mode, use the (+) & (-) button to adjust the TCR value.
- VPC Set up:** On the mode selection screen toggle to VRC, press and hold the FIRE button to enter the VPC mode. Press the FIRE button and use the (+) & (-) button to set the values to PL/P2/P3/P4/P5.
- Resistance and Puffs Reset:** Enter the setting state. Press the FIRE button to toggle the cursor to the COIL or PUFF. Press (+) to reset the COIL or PUFF value.
- Resistance lock:** Enter the setting state. Press the FIRE button to toggle the cursor to the COIL. Press (-) button to lock and unlock the resistance.
- Screen lock:** Press and hold (+) & (-) button simultaneously to Lock and Unlock the screen.
- Display brightness adjustment:** Press and hold the FIRE & (+) or (-) button simultaneously to adjust the brightness of the display.

English 104

Description of Warning

11. USB update: (Please see Diagram 11)

- Remove Atomizer.
- Remove the screws.
- Remove the cover plate.
- Remove the USB waterproof silicon cover to access the USB port.
- Hold down the FIRE button and insert the USB cable to a PC to perform the update operation.



Description of Warning

- NO COIL DETECTED:** No atomizer detected. Please check if the atomizer and coil is properly connected.
- PROTECTION ATOMIZER SHORT:** The atomizer is short circuited. Please check your coils for any shortage.
- ATOMIZER RESISTANCE HIGH:** Resistance of the atomizer is too high. Please check your coils.
- 10% CUT-OFF PROTECTION:** Output will automatically shut off after 10s.
- BATTERY LOW PROTECTION:** Battery voltage is low, please recharge your battery.
- BATTERY WEAK PLZ LOWER WATTAGE:** The battery is too weak, please check whether it is well connected / replace with a higher rated battery / lower the power setting or charge your battery.
- UNLOCK PRESS +&-:** Press the (+) & (-) button simultaneously to Unlock.
- DEVICE OVERHEAT PROTECTION:** Temperature of the PCB is over 75 °C, Please allow the device to cool down.

English 105

CUSTOMER SERVICE

- NO LIQUID:** Atomizer is dry, please add liquid.
- NEW + / 0.000 SAME -** When the NEW or OLD atomizer display occurs on TC mode, press (+) button to re-detect the resistance, press (-) button to select the previous resistance.

ATTENTION

- * Product is not intended for use by pregnant women and children under the age of 18
- * Keep away from fire
- * Avoid impact



Service in China

Main page: www.geekvape.com
Add: Xingye Rd. #3012, Bao'an District, Shenzhen, China
Email: support@geekvape.com
Available: Mon-Fri, 9AM to 6PM CST



Service in the USA

Main page: www.geekvapeusa.com
Add: 637 E Big Beaver Rd STE 211, Troy, Michigan, 48063 USA
Phone: 866-877-4335
Email: service@geekvapeusa.com
Available: Mon-Fri, 9AM to 5PM EST

English 106

ANTI-COUNTERFEITING QUERY

VISUAL METHOD

- Sway the label under light lightly.



- Logo will expand gradually to curved shape with the different viewing angle.



WEBSITE AUTHENTICITY CHECK

- Go to www.geekvape.com and scroll right to the bottom of the main page.
- Scratch the code and enter the 12 digit security numbers on the blank field.
- Click on the "Go" Button and a pop-up window should appear confirming if your product is authentic.



English 107