Qplus[™] LED SLIM POT LIGHT -

4 INCH 1CCT











LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Customizable with color trims

Effortless switch trims for a modern, seamless look in your space. More colors available.









QLED-DL4HA-TR-BZ











SKU	21104202	21104202 + 21101020
MODEL CODE	QLEDMB-4INCH- 9W(DM)	QLEDMB-4INCH-9W(DM) + QLED-DL4HA-TR-BK
COLOR TEMPERATURE	SINGLE CCT Select from 2700K / 3000K / 4000K / 5000K / 6500K	
CONTROLLED BY	Junction Box	
MEMORY FEATURE	No	
LOCATION	Damp	
AREA OF USE	Indoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	10W	
LUMENS	750LM	
CONNECTORS	TWC (Twist Wire Connector)	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









Oplus[™] LED SLIM POT LIGHT -

4 INCH 5CCT











LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.




Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Customizable with color trims

Effortless switch trims for a modern, seamless look in your space. More colors available.



















	-	
SKU	21104301	21104301 + 21101020
MODEL CODE	QLEDMB-4INCH- 9W(DM)-5C	QLEDMB-4INCH-9W(DM)-5C + QLED-DL4HA-TR-BK
COLOR TEMPERATURE	5 CCT Adjustable from 2700K, 3000K, 3500K, 4000K and 5000K to customize the lighting suitable for the space, mood or specific task	
CONTROLLED BY	Juncti	on Box
MEMORY FEATURE	No	
LOCATION	Damp	
AREA OF USE	Indoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Y	es
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	10W	
LUMENS	750LM	
CONNECTORS	TWC (Twist V	Vire Connector)
OPERATING TEMPERATURE	-20 °C / -4 °F t	o 40 °C / 104 °F









Qplus[™] LED SLIM POT LIGHT -

4 INCH 1CCT











LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Customizable with color trims

Effortless switch trims for a modern, seamless look in your Space. More colors available.









QLED-DL4HA-TR-BZ











SKU	21104602	21104602 + 21101020
MODEL CODE	QLEDMB-4INCH- 10W(DM)	QLEDMB-4INCH-10W(DM) + QLED-DL4HA-TR-BK
COLOR TEMPERATURE	SINGLE CCT Select from 2700K / 3000K / 4000K / 5000K / 6500K	
CONTROLLED BY	Junction Box	
MEMORY FEATURE	No	
LOCATION	Damp	
AREA OF USE	Indoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	10W	
LUMENS	750LM	
CONNECTORS	EZ (4 Port) Connectors	





OPERATING TEMPERATURE





-20 °C / -4 °F to 40 °C / 104 °F

Qplus[™] LED SLIM POT LIGHT -

4 INCH 4CS









Available in other colors:























Customize your color temperature with the wall switch Convenience to the next level!

Adjustable 4 different color temperatures any time of the day.



Memory Fuction

Save your chosen color temperature for easy access without the need to readjust every time.



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border


Wider border can fully cover and smoothly fit mounting holes.



Customizable with color trims

Effortless switch trims for a modern, seamless look in your space. More colors available.









SKU	21105301	21105301 + 21101020
MODEL CODE	QLEDMB-4INCH- 10W(DM)-4C-S	QLEDMB-4INCH-10W(DM)-4C- + QLED-DL4HA-TR-BK+BK
COLOR TEMPERATURE	4CS (4CCT + S Effortlessly switch between 300 using the junction box or y flexible lightin	our wall switch for a more
CONTROLLED BY	Juncti	on Box
MEMORY FEATURE	No	
LOCATION	Wet & Damp	
AREA OF USE	Indoors & Outdoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	10W	
LUMENS	750LM	
CONNECTORS	EZ (4 Port)	Connectors
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









Oplus[™] LED SLIM POT LIGHT -

4 INCH 5CCT









LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Customizable with color trims

Effortless switch trims for a modern, seamless look in your space. More colors available.

Available in other colors:



















SKU	21104801	21104801 + 21101020
MODEL CODE	QLEDMB-4INCH- 10W(DM)-5C	QLEDMB-4INCH-10W(DM)-5C + QLED-DL4HA-TR-BK
COLOR TEMPERATURE	5 C Adjustable from 2700K, 3000K to customize the lighting suitable f	K, 3500K, 4000K and 5000K
CONTROLLED BY	Junction Box	
MEMORY FEATURE	No	
LOCATION	Wet & Damp	
AREA OF USE	Indoors & Outdoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	10W	
LUMENS	750LM	
CONNECTORS	EZ (4 Port)	Connectors
OPERATING TEMPERATURE	-20 °C / -4 °F to	o 40 °C / 104 °F









Qplus[™] LED SLIM POT LIGHT -

6 INCH 1CCT









LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Install anywhere

Crafted to seamlessly fit into any ceiling, beneath any joist.





5 YEAR	WARRANTY

SKU	21105902	21105922
MODEL CODE	QLEDMB-6INCH- 13W(DM)	QLEDMB-6INCH- 13W(DM)
COLOR TEMPERATURE	SINGLE CCT Select from 2700K / 3000K / 4000K / 5000K / 6500K	
CONTROLLED BY	Junction Box	
MEMORY FEATURE	No	
LOCATION	Damp	
AREA OF USE	Indoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	13W	
LUMENS	1050LM	
CONNECTORS	EZ (4 Port) Connectors	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









DIUS LED SLIM POT LIGHT -

6 INCH 4CS









LEADING FEATURES:



Customize your color temperature with the wall switch

Convenience to the next level! Adjustable 4 different color temperatures any time of the day.



Memory Fuction

Save your chosen color temperature for easy access without the need to readjust every time.



Upgrade to WiFi Dimmer without changing your lights

Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.







		_
SKU	21105801	21105811
MODEL CODE	QLEDMB-6INCH- 13W(DM)-4C-S	QLEDMB-6INCH- 13W(DM)-4C-S
COLOR TEMPERATURE	4CS (4CCT + Switch Control) Effortlessly switch between 3000K, 4000K, 5000K or 6500K using the junction box or your wall switch for a more flexible lighting experience	
CONTROLLED BY	Juncti	on Box
MEMORY FEATURE	No	
LOCATION	Wet & Damp	
AREA OF USE	Indoors & Outdoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	13W	
LUMENS	1050LM	
CONNECTORS	EZ (4 Port) Connectors	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









Oplus[™] LED SLIM POT LIGHT -

6 INCH 5CCT









LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Install anywhere

Crafted to seamlessly fit into any ceiling, beneath any joist.







SKU	21105701	21105711
MODEL CODE	QLEDMB-6INCH- 13W(DM)-5C	QLEDMB-6INCH- 13W(DM)-5C
COLOR TEMPERATURE	5 CCT Adjustable from 2700K, 3000K, 3500K, 4000K and 5000K to customize the lighting suitable for the space, mood or specific task	
CONTROLLED BY	Juncti	on Box
MEMORY FEATURE	No	
LOCATION	Wet & Damp	
AREA OF USE	Indoors & Outdoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	13W	
LUMENS	1050LM	
CONNECTORS	EZ (4 Port) Connectors	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









OPIUS™ LED SLIM POT LIGHT -

8 INCH 4CS









LEADING FEATURES:



Customize your color temperature with the wall switch

Convenience to the next level! Adjustable 4 different color temperatures any time of the day.



Memory Fuction

Save your chosen color temperature for easy access without the need to readjust every time.



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital

& Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.





SKU	21102801
MODEL CODE	QLEDMB-8INCH- 18W(DM)-4C-S
COLOR TEMPERATURE	4CS (4CCT + Switch Control) Effortlessly switch between 3000K, 4000K, 5000K or 6500K using the junction box or your wall switch for a more flexible lighting experience
CONTROLLED BY	Junction Box
MEMORY FEATURE	No
LOCATION	Wet & Damp
AREA OF USE	Indoors & Outdoors
AIRTIGHT	Yes
BEAM ANGLE	140°
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	18W
LUMENS	1400LM
CONNECTORS	EZ (4 Port) Connectors
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F









OPIUS[™] LED SLIM POT LIGHT -

8 INCH 5CCT









LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Install anywhere

Crafted to seamlessly fit into any ceiling, beneath any joist.







SKU	21105701	21105711
MODEL CODE	QLEDMB-8INCH- 18W(DM)-5C	QLEDMB-8INCH- 18W(DM)-5C
COLOR TEMPERATURE	5 CCT Adjustable from 2700K, 3000K, 3500K, 4000K and 5000K to customize the lighting suitable for the space, mood or specific task	
CONTROLLED BY	Juncti	on Box
MEMORY FEATURE	No	
LOCATION	Wet & Damp	
AREA OF USE	Indoors & Outdoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	18W	
LUMENS	1400LM	
CONNECTORS	EZ (4 Port) Connectors	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









OPIUS[™] LED SLIM POT LIGHT -

4 INCH SMART















RGB with Warm to Cool Whites Design the perfect setting for gatherings, holidays, movies, and more from your phone.



WiFi Connected Lights Control light colors, temperature and brightness using your mobile phone



Hands-Free Voice Control Compatible with Amazon Alexa and Google Assistant.



ceiling shade

Customized to match

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Customizable with color trims

Effortless switch trims for a modern, seamless look in your space. More colors available.







SKU	21105201	21105202 + 21101020
MODEL CODE	QLEDMB-4INCH- 10W(DM)-RGBWF	QLEDMB-4INCH-10W(DM)-RGBWF + QLED-DL4HA-TR-BK
COLOR TEMPERATURE	SMART RGB LIGHT Provides a wide range of option from 16M colors, tunable white 2700K to 6500K with a seamless integration with your smart home set up	
CONTROLLED BY	Juncti	on Box
MEMORY FEATURE	No	
LOCATION	Wet & Damp	
AREA OF USE	Indoors & Outdoors	
AIRTIGHT	Yes	
BEAM ANGLE	140°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	10W	
LUMENS	750LM	
CONNECTORS	EZ (4 Port) Connectors	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









4 INCH 1CCT SLIM











LEADING FEATURES:

Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.





SKU	21104902	21105002
MODEL CODE	QLEDRT-4INCH- 10W(DM)	QLEDTR-4INCH- 10W(DM)
COLOR TEMPERATURE	SINGL Select 2700K / 3000K / 400	from
CONTROLLED BY	Juncti	on Box
MEMORY FEATURE	N	lo
LOCATION	Damp	
AREA OF USE	Indoors	
AIRTIGHT	N	lo
NARROW GAP	No	
BEAM ANGLE	4	0°
DIMMABLE	Y	es
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	10)W
LUMENS	750	DLM
OPERATING TEMPERATURE	-20 °C / -4 °F to	o 40 °C / 104 °F









4 INCH 1CCT AIRTIGHT











LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.



Crafted for efficient energy conservation

Efficient insulation and sealed gimbals cut energy costs and maintain even temperatures on all floors.





SKU	21101602
MODEL CODE	QLEDRT-4INCH-10W(DM)
COLOR TEMPERATURE	SINGLE CCT Select from 2700K / 3000K / 4000K / 5000K
CONTROLLED BY	Junction Box
MEMORY FEATURE	No
LOCATION	Damp
AREA OF USE	Indoors
AIRTIGHT	Yes
NARROW GAP	No
BEAM ANGLE	40°
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	10W
LUMENS	750LM
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F









4 INCH 1CCT NARROW GAP











Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.



Ultra narrow gap

For a seamless and more sofisticated look for you space.





SKU	21100722
MODEL CODE	QLEDRT-4INCH-10W(DM) N
COLOR TEMPERATURE	SINGLE CCT Select from 3000K / 4000K / 5000K / 6500K
CONTROLLED BY	Junction Box
MEMORY FEATURE	No
LOCATION	Damp
AREA OF USE	Indoors
AIRTIGHT	No
NARROW GAP	Yes
BEAM ANGLE	40°
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	10W
LUMENS	750LM
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F









Oplus LED SLIM GIMBAL LIGHT -

4 INCH 1CCT AIRTIGHT NARROW GAP









LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.



Crafted for efficient energy conservation

Efficient insulation and sealed gimbals cut energy costs and maintain even temperatures on all floors.





SKU	21101622
MODEL CODE	QLEDRT-4INCH-10W(DM) AT N
COLOR TEMPERATURE	SINGLE CCT Select from 3000K / 4000K / 5000K / 6500K
CONTROLLED BY	Junction Box
MEMORY FEATURE	No
LOCATION	Damp
AREA OF USE	Indoors
AIRTIGHT	Yes
NARROW GAP	Yes
BEAM ANGLE	40°
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	10W
LUMENS	750LM
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F









4 INCH 4CS SLIM











LEADING FEATURES:



Customize your color temperature with the wall switch

Convenience to the next level! Adjustable 4 different color temperatures any time of the day.



Memory Fuction

Save your chosen color temperature for easy access without the need to readjust every time.



Upgrade to WiFi Dimmer without changing your lights

Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.







EAR	WARRANTY

SKU	21105501	21105511
MODEL CODE	QLEDRT-4INCH- 10W(DM)-4C-S N	QLEDTR-4INCH- 10W(DM)-4C-S N
COLOR TEMPERATURE	4CS (4CCT + S Effortlessly switch between 300 using the junction box or y flexible lightin	our wall switch for a more
CONTROLLED BY	Juncti	on Box
MEMORY FEATURE	Y	es
LOCATION	Wet 8	k Damp
AREA OF USE	Indoors 8	Outdoors
AIRTIGHT	N	lo
NARROW GAP	1	lo
BEAM ANGLE	4	0°
DIMMABLE	Y	es
COMPATIBLE WITH DIMMERS	Y	es
WATTAGE	10	ow .
LUMENS	75	OLM
OPERATING TEMPERATURE	-20 °C / -4 °F to	o 40 °C / 104 °F









4 INCH 4CS AIRTIGHT











LEADING FEATURES:



Customize your color temperature with the wall switch

Convenience to the next level! Adjustable 4 different color temperatures any time of the day.



Memory Fuction

Save your chosen color temperature for easy access without the need to readjust every time.



Upgrade to WiFi Dimmer without changing your lights

Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.



Crafted for efficient energy conservation

Efficient insulation and sealed gimbals cut energy costs and maintain even temperatures on all floors.





21105611

5 YEAR WARRANTY

SKU

MODEL CODE QLEDRT-4INCH- 10W(DM)-4C-S AT N 10W(DM)-4C-S AT		4CS (4CCT + S	witch Control)
	MODEL CODE		

21105601

OPERATING TEMPERATURE

COLOR TEMPERATURE	Effortlessly switch between 3000K, 4000K, 5000K or 6500K using the junction box or your wall switch for a more flexible lighting experience
CONTROLLED BY	Junction Box
MEMORY FEATURE	Yes
LOCATION	Wet & Damp
AREA OF USE	Indoors & Outdoors
AIRTIGHT	Yes
NARROW GAP	No
BEAM ANGLE	40°
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	10W
LUMENS	750LM









-20 °C / -4 °F to 40 °C / 104 °F

Oplus LED SLIM GIMBAL LIGHT -

4 INCH 4CS NARROW GAP











Customize your color temperature with the wall switch

Convenience to the next level! Adjustable 4 different color temperatures any time of the day.



Memory Fuction

Save your chosen color temperature for easy access without the need to readjust every time.



Upgrade to WiFi Dimmer without changing your lights

Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.



Ultra narrow gap

For a seamless and more sofisticated look for you space.





ARRANTY	
SKU	21102701

SKU	21102701
MODEL CODE	QLEDRT-4INCH-10W(DM)-4C-S N
COLOR TEMPERATURE	4CS (4CCT + Switch Control) Effortlessly switch between 3000K, 4000K, 5000K or 6500K using the junction box or your wall switch for a more flexible lighting experience
CONTROLLED BY	Junction Box
MEMORY FEATURE	Yes
LOCATION	Wet & Damp
AREA OF USE	Indoors & Outdoors
AIRTIGHT	No
NARROW GAP	Yes
BEAM ANGLE	40°
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	10W
LUMENS	750LM
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F









Oplus LED SLIM GIMBAL LIGHT -

4 INCH 4CS NARROW GAP AIRTIGHT







LEADING FEATURES:



Customize your color temperature with the wall switch

Convenience to the next level! Adjustable 4 different color temperatures any time of the day.



Memory Fuction

Save your chosen color temperature for easy access without the need to readjust every time.



Upgrade to WiFi Dimmer without changing your lights

Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.



SAVE

ENERGY

Crafted for efficient energy conservation

Efficient insulation and sealed gimbals cut energy costs and maintain even temperatures on all floors.



SKU



21102711

MODEL CODE	QLEDRT-4INCH-10W(DM)-4C-S AT N	
COLOR TEMPERATURE	4CS (4CCT + Switch Control) Effortlessly switch between 3000K, 4000K, 5000K or 6500K using the junction box or your wall switch for a more flexible lighting experience	
CONTROLLED BY	Junction Box	
MEMORY FEATURE	Yes	
LOCATION	Wet & Damp	

	'
AREA OF USE	Indoors & Outdoors
AIRTIGHT	Yes
NARROW GAP	Yes
BEAM ANGLE	40°
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	10W



For a seamless and more sofisticated look for you space.







LUMENS

OPERATING TEMPERATURE





750LM

-20 °C / -4 °F to 40 °C / 104 °F

4 INCH 5CCT SLIM











LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.



SKU





21106001	21106011
QLEDRT-4INCH- 10W(DM)-5C	QLEDTR-4INCH- 10W(DM)-5C

MODEL CODE	QLEDRT-4INCH- 10W(DM)-5C	QLEDTR-4INCH- 10W(DM)-5C
COLOR TEMPERATURE	5 CCT Adjustable from 2700K, 3000K, 3500K, 4000K and 5000K to customize the lighting suitable for the space, mood or specific tas	
CONTROLLED BY	Juncti	on Box
MEMORY FEATURE	1	No
LOCATION	Wet & Damp	
AREA OF USE	Indoors & Outdoors	
AIRTIGHT	No	
NARROW GAP	No	
BEAM ANGLE	40°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	10W	
LUMENS	750LM	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









4 INCH 5CCT AIRTIGHT











LEADING FEATURES:

Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.



Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.



Crafted for efficient energy conservation

Efficient insulation and sealed gimbals cut energy costs and maintain even temperatures on all floors.







SKU	21104101	21104111	
MODEL CODE	QLEDRT-4INCH- 10W(DM)-5C AT	QLEDTR-4INCH- 10W(DM)-5C AT	
COLOR TEMPERATURE	5 CCT Adjustable from 2700K, 3000K, 3500K, 4000K and 5000K to customize the lighting suitable for the space, mood or specific tas		
CONTROLLED BY	Juncti	on Box	
MEMORY FEATURE	1	No	
LOCATION	Wet & Damp		
AREA OF USE	Indoors & Outdoors		
AIRTIGHT	Yes		
NARROW GAP	No		
BEAM ANGLE	40°		
DIMMABLE	Yes		
COMPATIBLE WITH DIMMERS	Yes		
WATTAGE	10W		
LUMENS	750LM		
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F		









4 INCH SMART











LEADING FEATURES:

RGB with Warm to Cool Whites Design the perfect setting for gatherings, holidays, movies, and more from your phone.



WiFi Connected Lights Control light colors,

temperature and brightness using your mobile phone



Hands-Free Voice Control

Compatible with Amazon Alexa and Google Assistant.



Customized to match ceiling shade

Designed to look seamless with the common ceiling shade.




Wider and smooth border

Wider border can fully cover and smoothly fit mounting holes.



Enhanced eye comfort

Narrow light angle, ensuring a comfortable and soothing environment for the eyes.



Ultra narrow gap

For a seamless and more sofisticated look for you space.







SKU	21103511	21103512
MODEL CODE	QLEDRT-4INCH- 10W(DM)-RGBWF	QLEDRT-4INCH- 10W(DM)-RGBWF
	SMART RGB LIGHT	

	SMART RGB LIGHT	
COLOR TEMPERATURE	Provides a wide range of option from 16M colors, tunable white 2700K to 6500K with a seamless integration with your smart home set up	
CONTROLLED BY	Junction Box	
MEMORY FEATURE	No	
LOCATION	Wet & Damp	
AREA OF USE	Indoors & Outdoors	
AIRTIGHT	No	
NARROW GAP	Yes	
BEAM ANGLE	40°	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	10W	
LUMENS	750LM	



WORKS WITH amazon alexa

works with

Google Assistant



OPERATING TEMPERATURE





-20 °C / -4 °F to 40 °C / 104 °F

7.5 DISK LIGHT 1CCT









Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install

Simple and hassle-free installation.







SKU	21100802	21100812	21100822
MODEL CODE	QLEDDK-7.5INCH -15WH	QLEDDK-7.5INCH -15SL	QLEDDK-7.5INCH -15BZ
COLOR TEMPERATURE	SINGLE CCT Select from 3000K / 4000K / 5000K		
CONTROLLED BY		Junction Box	
MEMORY FEATURE	No		
LOCATION	Damp		
AREA OF USE	Indoors		
DIMENSION	D 7.5" x H 1.2"		
CRI	80+		
DIMMABLE	Yes		
COMPATIBLE WITH DIMMERS	Yes		
WATTAGE	15W		





LUMENS

CONNECTORS

OPERATING TEMPERATURE





1050LM

TWC (Twist Wire Connector)

-20 °C / -4 °F to 40 °C / 104 °F

7.5 DISK LIGHT 3CS







LEADING FEATURES:



Customize your color temperature with the wall switch

Convenience to the next level! Adjustable 4 different color temperatures any time of the day.



Memory Fuction

Save your chosen color temperature for easy access without the need to readjust every time.



Upgrade to WiFi Dimmer without changing your lights

Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light




Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install





SKU	21100809		
MODEL CODE	QLEDDK-7.5INCH-15WH-4S		
COLOR TEMPERATURE	3CS (3CCT + Switch Control) Effortlessly switch between 3000K, 4000K or 5000K using the junction box or your wall switch for a more flexible lighting experience		
CONTROLLED BY	Junction Box		
MEMORY FEATURE	Yes		
LOCATION	Damp		
AREA OF USE	Indoors		
DIMENSION	D 7.5" x H 1.2"		
CRI	80+		
DIMMABLE	Yes		
COMPATIBLE WITH DIMMERS	Yes		
WATTAGE	15W		
LUMENS	1050LM		
CONNECTORS	TWC (Twist Wire Connector)		
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F		









7.5 DISK LIGHT 5CCT











Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install





SKU	21100807	
MODEL CODE	QLEDDK-7.5INCH-15WH-5CCT	
COLOR TEMPERATURE	5 CCT Adjustable from 2700K, 3000K, 3500K, 4000K and 5000K to customize the lighting suitable for the space, mood or specific task	
CONTROLLED BY	Junction Box	
MEMORY FEATURE	No	
LOCATION	Damp	
AREA OF USE	Indoors	
DIMENSION	D 7.5" x H 1.2"	
CRI	80+	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	15W	
LUMENS	1050LM	
CONNECTORS	TWC (Twist Wire Connector)	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









FLUSH MOUNT - 12IN DOUBLE RING 1CCT











Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install







SKU	21100502	21100512	
MODEL CODE	QLED-FM12TD18W-	QLED-FM12TD18W-	
COLOR TEMPERATURE	SINGLE CCT Select from 3000K / 4000K / 5000K / 6500K		
CONTROLLED BY	Junctio	on Box	
MEMORY FEATURE	No		
LOCATION	Damp		
AREA OF USE	Indoors		
DIMENSION	D 12" x H 3.5"		
CRI	80+		
DIMMABLE	Yes		
COMPATIBLE WITH DIMMERS	Yes		
WATTAGE	18W		
LUMENS	1200LM		
CONNECTORS	TWC (Twist Wire Connector)		
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F		









FLUSH MOUNT - 14IN DOUBLE RING 1CCT











Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install







SKU	21100602	21100612	
MODEL CODE	QLED-FM14TD25W-	QLED-FM14TD25W-	
COLOR TEMPERATURE	SINGLE CCT Select from 3000K / 4000K / 5000K / 6500K		
CONTROLLED BY	Junctio	on Box	
MEMORY FEATURE	No		
LOCATION	Damp		
AREA OF USE	Indoors		
DIMENSION	D 14" x H 4"		
CRI	80+		
DIMMABLE	Yes		
COMPATIBLE WITH DIMMERS	Yes		
WATTAGE	25W		
LUMENS	1750LM		
CONNECTORS	TWC (Twist Wire Connector)		
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F		









FLUSH MOUNT - 15IN DOUBLE RING 1CCT











Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install







SKU	21100402	21100412
MODEL CODE	QLED-FM15TD25W-	QLED-FM15TD25W-
COLOR TEMPERATURE	SINGLE CCT Select from 3000K / 4000K / 5000K / 6500K	
CONTROLLED BY	Junctio	on Box
MEMORY FEATURE	No	
LOCATION	Damp	
AREA OF USE	Indoors	
DIMENSION	D 15" x H 4"	
CRI	80+	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	25W	
LUMENS	1750LM	
CONNECTORS	TWC (Twist Wire Connector)	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









FLUSH MOUNT - 12IN DOUBLE RING 5CCT











Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install





SKU	21100701
MODEL CODE	QLED-FM12TD18W-5CS
COLOR TEMPERATURE	5 CCT Adjustable from 3000K, 3500K, 4000K, 5000K and 6500K to customize the lighting suitable for the space, mood or specific task
CONTROLLED BY	Junction Box
MEMORY FEATURE	No
LOCATION	Damp
AREA OF USE	Indoors
DIMENSION	D 12" x H 3.5"
CRI	80+
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	18W
LUMENS	1200LM
CONNECTORS	TWC (Twist Wire Connector)
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F









FLUSH MOUNT - 14IN DOUBLE RING 5CCT











Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install





SKU	21100702
MODEL CODE	QLED-FM14TD25W-5CS
COLOR TEMPERATURE	5 CCT Adjustable from 3000K, 3500K, 4000K, 5000K and 6500K to customize the lighting suitable for the space, mood or specific task
CONTROLLED BY	Junction Box
MEMORY FEATURE	No
LOCATION	Damp
AREA OF USE	Indoors
DIMENSION	D 14" x H 4"
CRI	80+
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	25W
LUMENS	1750LM
CONNECTORS	TWC (Twist Wire Connector)
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F









FLUSH MOUNT - 12IN DOUBLE RING 1CCT











Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install





SKU	21101602
MODEL CODE	QLED-FM12TD18W-
COLOR TEMPERATURE	SINGLE CCT Select from 3000K / 4000K / 5000K / 6500K
CONTROLLED BY	Junction Box
MEMORY FEATURE	No
LOCATION	Damp
AREA OF USE	Indoors
DIMENSION	D 12" x H 3.5"
CRI	80+
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	18W
LUMENS	1200LM
CONNECTORS	TWC (Twist Wire Connector)
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F









FLUSH MOUNT - 14IN DOUBLE RING 1CCT





LEADING FEATURES:





Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Built with Premium Lens

For soft and transparent lighting that does not turn yellow over time



Easy to Install





21101702
QLED-FM14TD25W-
SINGLE CCT Select from 3000K / 4000K / 5000K / 6500K
Junction Box
No
Damp
Indoors
D 14" x H 4"
80+
Yes
Yes
25W
1750LM
TWC (Twist Wire Connector)









SEMI FLUSH MOUNT -16IN CARVING DRUM SHADE 5CCT











Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Switchable Color Temperature in 1 Single Unit

5 color temperatures to choose from to suit your space or preference



Easy to Install







SKU	21201001	21201002
MODEL CODE	QLEDFM-JF15-2-BN	QLEDFM-JF15-2-BZ
COLOR TEMPERATURE	5 CCT Adjustable from 3000K, 3500K, 4000K, 5000K and 6500K to customize the lighting suitable for the space, mood or specific tas	
CONTROLLED BY	Junction	Вох
MEMORY FEATURE	No	
LOCATION	Damp	
AREA OF USE	Indoors	
DIMENSION	D 16" x H 12"	
CRI	80-1	
DIMMABLE	Yes	
COMPATIBLE WITH DIMMERS	Yes	
WATTAGE	25W	
LUMENS	1850LM	
CONNECTORS	TWC (Twist Wi	re Connector)
OPERATING TEMPERATURE	-20 °C / -4 °F to	o 40 °C / 104 °F









FLUSH MOUNT -VINTAGE CEILING LIGHT



LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights

Compatible to LED WiFi, Digital & Analog Dimmers.



Premium Quality & Elegant Style

Built with thickened metal and industrial cage that does not deform.



QUALITY

E26 Socket for Better Compatibility

Can be used with E26 Base LED Bulbs, CFL & Incandescent Bulbs.



Easy to Install







SKU	21201106	21201105	
MODEL CODE	QLED-PMFM06-2L-BK QLED-PMFM05-3		
COLOR TEMPERATURE	SINGLE CCT ST19 BULBS Select from 3000K / 4000K / 5000K		
CONTROLLED BY	Juncti	on Box	
NO, OF BULBS	2 X ST19 BULB	3 X ST19 BULB	
LOCATION	Damp		
AREA OF USE	Indoors		
DIMENSION	D 12.6" x H 5.13" D 15" x H 5.88"		
CRI	80+		
DIMMABLE	Yes		
COMPATIBLE WITH DIMMERS	Yes		
WATTAGE	2 X 7W 3 X 7W		
LUMENS	2 X 800LM 3 X 800LM		
CONNECTORS	TWC (Twist Wire Connector)		
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F		









SEMI FLUSH MOUNT -VINTAGE CEILING LIGHT







Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Premium Quality & Elegant Style

Built with thickened metal and industrial cage that does not deform.



E26 Socket for Better Compatibility

Can be used with E26 Base LED Bulbs, CFL & Incandescent Bulbs.



Easy to Install







SKU	21201104	21201103	
MODEL CODE	QLED-PMFM04-2L-BK QLED-PMFM03-		
COLOR TEMPERATURE	SINGLE CCT ST19 BULBS Select from 3000K / 4000K / 5000K		
CONTROLLED BY	Juncti	on Box	
NO, OF BULBS	2 X ST19 BULB 3 X ST19 BUL		
LOCATION	Damp		
AREA OF USE	Indoors		
DIMENSION	D 12" x H 7.25" D 14.25" x H 8"		
CRI	8	0+	
DIMMABLE	Yes		
COMPATIBLE WITH DIMMERS	Yes		
WATTAGE	2 X 7W 3 X 7W		
LUMENS	2 X 800LM 3 X 800LM		
CONNECTORS	TWC (Twist Wire Connector)		
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F		









9" MOTION SENSOR LIGHT 4CS





LEADING FEATURES:



Customize your color temperature with the wall switch Convenience to the next level!

Adjustable 4 different color temperatures any time of the day.



Memory Fuction

Save your chosen color temperature for easy access without the need to readjust every time.



Upgrade to WiFi Dimmer without changing your lights

Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Motion Sensor Control

Light will automatically turn on when motion detected.



Easy to Install







SKU	21201301	21201302	21201303
MODEL CODE	QLEDFM-8.5inch -16W(MS)-4C WH	QLEDFM-8.5inch -16W(MS)-4C SL	QLEDFM-8.5inch -16W(MS)-4C BZ
	4CS (4CCT + Switch Control)		

	4CS (4CCT + Switch Control)
COLOR TEMPERATURE	Effortlessly switch between 3000K, 4000K, 5000K or 6500K using the junction box or your wall switch for a more flexible lighting experience
CONTROLLED BY	Motion Sensor
MEMORY FEATURE	Yes
LOCATION	Damp
AREA OF USE	Indoors
DIMENSION	D 8.75" x H 0.7"
CRI	80+
DIMMABLE	Yes
COMPATIBLE WITH DIMMERS	Yes
WATTAGE	16W
LUMENS	1100LM
CONNECTORS	TWC (Twist Wire Connector)
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F









LED Circular Module Panel 1CCT





LEADING FEATURES:



Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Even Cast Lights

Enjoy an evenly lit room without anyshadows or dead spot caused by thegaps on your bulbs.



Easy to Install

Simple and Magnet installation.









SKU				
COLOR TEMPERATURE	SKU	11400102	11400202	11400302
COLOR TEMPERATURE Select from 3000K / 4000K / 5000K CONTROLLED BY Junction Box MEMORY FEATURE No LOCATION Damp AREA OF USE Indoors DIMENSION D 4.1" x H 0.63" D 5" x H 0.63" D 7" x H 0.79" CRI 80+ DIMMABLE Yes COMPATIBLE WITH DIMMERS Yes WATTAGE 12W 16W 24W LUMENS 750LM 1250LM 2100LM CONNECTORS TWC (Twist Wire Connector)	MODEL CODE			
MEMORY FEATURE No LOCATION Damp AREA OF USE Indoors DIMENSION D 4.1" x H 0.63" D 5" x H 0.63" D 7" x H 0.79" CRI 80+ DIMMABLE Yes COMPATIBLE WITH DIMMERS Yes WATTAGE 12W 16W 24W LUMENS 750LM 1250LM 2100LM CONNECTORS TWC (Twist Wire Connector)	COLOR TEMPERATURE	30	Select from	DK
LOCATION Damp AREA OF USE Indoors DIMENSION D 4.1" x H 0.63" D 5" x H 0.63" D 7" x H 0.79" CRI 80+ DIMMABLE Yes COMPATIBLE WITH DIMMERS Yes WATTAGE 12W 16W 24W LUMENS 750LM 1250LM 2100LM CONNECTORS TWC (Twist Wire Connector)	CONTROLLED BY		Junction Box	
AREA OF USE Indoors	MEMORY FEATURE	No		
DIMENSION D 4.1" x H 0.63" D 5" x H 0.63" D 7" x H 0.79" CRI 80+ DIMMABLE Yes COMPATIBLE WITH DIMMERS Yes WATTAGE 12W 16W 24W LUMENS 750LM 1250LM 2100LM CONNECTORS TWC (Twist Wire Connector)	LOCATION	Damp		
CRI 80+ DIMMABLE Yes COMPATIBLE WITH DIMMERS Yes WATTAGE 12W 16W 24W LUMENS 750LM 1250LM 2100LM CONNECTORS TWC (Twist Wire Connector)	AREA OF USE	Indoors		
DIMMABLE Yes COMPATIBLE WITH DIMMERS Yes WATTAGE 12W 16W 24W LUMENS 750LM 1250LM 2100LM CONNECTORS TWC (Twist Wire Connector)	DIMENSION	D 4.1" x H 0.63"	D 5" x H 0.63"	D 7" x H 0.79"
COMPATIBLE WITH DIMMERS WATTAGE 12W 16W 24W LUMENS 750LM 1250LM 2100LM CONNECTORS TWC (Twist Wire Connector)	CRI		80+	
WATTAGE 12W 16W 24W LUMENS 750LM 1250LM 2100LM CONNECTORS TWC (Twist Wire Connector)	DIMMABLE	Yes		
LUMENS 750LM 1250LM 2100LM CONNECTORS TWC (Twist Wire Connector)	COMPATIBLE WITH DIMMERS	Yes		
CONNECTORS TWC (Twist Wire Connector)	WATTAGE	12W 16W 24W		
	LUMENS	750LM	1250LM	2100LM
OPERATING TEMPERATURE -20 °C / -4 °F to 40 °C / 104 °F	CONNECTORS	TWC (Twist Wire Connector)		
	OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F		









Oplus[™] RETROFIT LIGHTS

LED Circular Module Panel 3CCT









Upgrade to WiFi Dimmer without changing your lights Compatible to LED WiFi, Digital & Analog Dimmers.



Energy Saving

Integrated LED design saves 85% of energy than incandescent light



Even Cast Lights

Enjoy an evenly lit room without anyshadows or dead spot caused by thegaps on your bulbs.



Easy to Install

Simple and Magnet installation.







SKU	11400401	11400501	
MODEL CODE	KCJKK30X2W -240 GGU	KCJKK42X2W -310 GGU	
COLOR TEMPERATURE	3 CCT Adjustable from 3000K, 4000K and 5000K to customize the lighting suitable for the space, mood or specific task		
CONTROLLED BY	Juncti	on Box	
MEMORY FEATURE	N	No	
LOCATION	Damp		
AREA OF USE	Indo	oors	
DIMENSION	D 9.4" x H 0.79" D 12.2" x H 0.79"		
CRI	8	0+	
DIMMABLE	Yes		
COMPATIBLE WITH DIMMERS	Yes		
WATTAGE	32W 42W		
LUMENS	2500LM 4000LM		
CONNECTORS	TWC (Twist Wire Connector)		
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F		











3WAY 2ND GENERATION DIMMER SWITCH





LEADING FEATURES:



DIGITAL CIRCUIT. **ACCURATE DIMMING**

You wouldn't worry about the flickering of lights while dimming.



SENSITIVITY SLIDER

Adjust the dimming sensitivity or disable the dimming.



SMOOTH TRANSITION

Smooth Dimming from 10% to 100% without flicking and buzzing.



UNIVERSAL COMPATIBILITY

Compatible with most type of lights.



Easy to Install

Simple and hassle-free installation.





SKU	41100104	41100105
MODEL CODE	BAK-004AG	BAK-004AG
UNIVERSAL COMPATIBILITY	600W Incandescent Bulb / Halogen Bulb 150W Dimmable CFL /LED	
WITH WALL PLATE	N	o
FIREPROOF MATERIAL	Yes	
LOCATION	Damp	
AREA OF USE	Indoors	
DIMENSION	L 4.18" x W 1.8" x H 1.75"	
CONTROL CIRCUIT	Digital Circuit	
DIMMING RANGE	10% - 100%	
3 - WAYS	Yes	
CONNECTORS	TWC (Twist Wire Connector)	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	











3WAY 2ND GENERATION DIMMER SWITCH





LEADING FEATURES:



DIGITAL CIRCUIT. **ACCURATE DIMMING**

You wouldn't worry about the flickering of lights while dimming.



SENSITIVITY SLIDER

Adjust the dimming sensitivity or disable the dimming.



SMOOTH TRANSITION

Smooth Dimming from 10% to 100% without flicking and buzzing.



UNIVERSAL COMPATIBILITY

Compatible with most type of lights.



Easy to Install

Simple and hassle-free installation.



SKU	41100102	
MODEL CODE	BAK-004AG	
UNIVERSAL COMPATIBILITY	600W Incandescent Bulb / Halogen Bulb 150W Dimmable CFL /LED	
WITH WALL PLATE	Yes	
FIREPROOF MATERIAL	Yes	
LOCATION	Damp	
AREA OF USE	Indoors	
DIMENSION	L 4.7" x W 2.6" x H 1.75"	
CONTROL CIRCUIT	Digital Circuit	
DIMMING RANGE	10% - 100%	
3 - WAYS	Yes	
CONNECTORS	TWC (Twist Wire Connector)	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









Qplus[™] wiring devices

3WAY DIMMER SWITCH





LEADING FEATURES:



SENSITIVITY SLIDER

Adjust the dimming sensitivity or disable the dimming.



SMOOTH TRANSITION

Smooth Dimming from 10% to 100% without flicking and buzzing.



UNIVERSAL COMPATIBILITY

Compatible with most type of lights.



Easy to Install





SKU	41100101	
MODEL CODE	BAK-004A	
UNIVERSAL COMPATIBILITY	600W Incandescent Bulb / Halogen Bulb 150W Dimmable CFL /LED	
WITH WALL PLATE	Yes	
FIREPROOF MATERIAL	Yes	
LOCATION	Damp	
AREA OF USE	Indoors	
DIMENSION	L 4.7" x W 2.6" x H 1.75"	
CONTROL CIRCUIT	Analog Circuit	
DIMMING RANGE	10% - 100%	
3 - WAYS	Yes	
CONNECTORS	TWC (Twist Wire Connector)	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









OPIUS[™] WIRING DEVICES

GFCI RECEPTACLE OUTLET





LEADING FEATURES:



TAMPER RESISTANT

Provides a permanent solution to childhood shock caused by tampering with electrical outlets.



MULTI-PORT WIRING

2 ports at the side and 4 ports at the back for wiring multiple outlets.



SAFE CONTACT PLUG

The GFCI can protects other receptacles/outlets in the circuit.



END-OF-LIFE INDICATOR

GFCI includes an end-of-life monitoring function.



Easy to Install

Simple and hassle-free installation.





SKU	41100203	41100204
MODEL CODE	BAS-004WR	BAS-005WR
OUTLET POWER	15A / 1875W	20A / 2500W
WITH WALL PLATE	No	
FIREPROOF MATERIAL	Yes	
LOCATION	Damp / Wet	
AREA OF USE	Indoors / Outdoor	
DIMENSION	L 4.14" x W 1.68" x H 1.62"	
TAMPER RESISTANT	Yes	
WEATHER RESISTANT	Yes	
END OF LIFE ALARM	Yes	
CONNECTORS	Multi-Port Wiring	
OPERATING TEMPERATURE	-20 °C/-4 °F to 40 °C/104 °F	









OPIUS[™] WIRING DEVICES

USB OUTLET





LEADING FEATURES:



TAMPER RESISTANT

Provides a permanent solution to childhood shock caused by tampering with electrical outlets.



MULTI-PORT WIRING

2 ports at the side and 2 ports at the back for wiring multiple outlets.



OVERLOAD PROTECTION

Automatically shuts down to protect your devices once it has reached the maximum capacity of loads.



PLUG AND CHARGE

All you need is a USB cable to connect to the USB Type-A port or USB Type-C port.



Easy to Install

Simple and hassle-free installation.



SKU	41100303	
MODEL CODE	BAA-015	
USB POWER	Total 4.8A	
OUTLET POWER	15A / 1875W	
WITH WALL PLATE	No	
FIREPROOF MATERIAL	Yes	
LOCATION	Damp	
AREA OF USE	Indoors	
DIMENSION	L 4.14" x W 1.68" x H 1.77"	
TAMPER RESISTANT	Yes	
OVERLOAD PROTECTION	Yes	
CONNECTORS	Multi-Port Wiring	
OPERATING TEMPERATURE	-20 °C/-4 °F to 40 °C/104 °F	









Qplus[™] wiring devices

USB OUTLET





LEADING FEATURES:



TAMPER RESISTANT

Provides a permanent solution to childhood shock caused by tampering with electrical outlets.



MULTI-PORT WIRING

2 ports at the side and 4 ports at the back for wiring multiple outlets.



SLIM-MODERN DESIGN

For maximum wiring room to pair with other switches or outlets.



Easy to Install

Simple and hassle-free installation.





SKU	41100601	41100602
MODEL CODE	YGB-047	YGB-050
OUTLET POWER	15A / 1875W	20A / 2500W
WITH WALL PLATE	N	0
FIREPROOF MATERIAL	Yes	
LOCATION	Damp	
AREA OF USE	Indoors	
DIMENSION	L 4.13" × W 1.34" × H 0.95"	
TAMPER RESISTANT	Yes	
WEATHER RESISTANT	No	
END OF LIFE ALARM	No	
CONNECTORS	Multi-Port Wiring	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	









Qplus[™] wiring devices

OUTLET





LEADING FEATURES:



LARGE PADDLE Easy opening / closing of the



MULTI-PORT WIRING

2 ports at the side and 4 ports at the back for wiring multiple outlets.



SLIM-MODERN DESIGN

For maximum wiring room to pair with other switches or outlets.



Easy to Install



10	
2 YEAR	WARRANTY



SKU	41100501	41100502
MODEL CODE	YGD-003	BAK-002
SINGLE POLE / 3 - WAY	Single Pole	3 - Way
WITH WALL PLATE	No	
FIREPROOF MATERIAL	Yes	
LOCATION	Damp	
AREA OF USE	Indoors	
DIMENSION	L 4.13" x W 1.34" x H 1.26"	
TAMPER RESISTANT	Yes	
WEATHER RESISTANT	No	
END OF LIFE ALARM	No	
CONNECTORS	Multi-Port Wiring	
OPERATING TEMPERATURE	-20 °C / -4 °F to 40 °C / 104 °F	











SCREWLESS WALL PLATE








UNBREAKABLE MATERIAL Provide the durability and resilience needed to resist heavy impacts.



FIREPROOF MATERIAL

Flame Resistant No Fire Hazard, Rated V-2 per UL94.



UNIVERSAL COMPATIBILITY

Compatible with Decor, Light Switch, GFCI Outlet, etc



CHILD SAFE

100% Child Safe - No screws for kids to remove




Easy to Install





SKU	41100404	41100401
MODEL CODE	YGC-009-NS	YGC-004-NS
FIREPROOF MATERIAL	Y	es
UNBREAKABLE MATERIAL	Yes	
CHILD SAFE INVISIBLE SCREWS	Yes	
DIMENSION	W 2.93" x H 4.68"	W 4.73" x H 4.68"



SKU	41100402	41100403
MODEL CODE	YGC-005-NS	YGC-006-NS
FIREPROOF MATERIAL	Y	es
UNBREAKABLE MATERIAL	Yes	
CHILD SAFE INVISIBLE SCREWS	Yes	
DIMENSION	W 6.54" x H 4.68"	W 8.35" x H 4.68"









Oplus[™] wiring devices

SCREW WALL PLATE





LEADING FEATURES:

Provide the durability and resilience needed to resist heavy impacts.



FIREPROOF MATERIAL

Flame Resistant No Fire Hazard, Rated V-2 per UL94.



UNIVERSAL COMPATIBILITY

Compatible with Decor, Light Switch, GFCI Outlet, etc




Easy to Install





SKU	41100705	41100700
MODEL CODE	YGC-009 BK	YGC-009
FIREPROOF MATERIAL	Y	es
UNBREAKABLE MATERIAL	Yes	
CHILD SAFE INVISIBLE SCREWS	No	
DIMENSION	W 2.75" x H 4.5"	W 2.75" x H 4.5"





SKU	41100702	41100703
MODEL CODE	YGC-005	YGC-006
FIREPROOF MATERIAL	Y	es
UNBREAKABLE MATERIAL	Yes	
CHILD SAFE INVISIBLE SCREWS	No	
DIMENSION	W 4.57" x H 4.5"	W 6.4" x H 4.5"







