

Accu1 Direct

Insulation Blowing Machines & Removal Vacuums

Accu1 9800

Insulation Blowing Machine



The Accu1 9800 is a portable, all fiber, blowing machine. It utilizes a heavy-duty steel gauge auger that can cut through and provide superior agitation for any type of material. Its horizontal feed and circular conditioning create a continual flow of material with no jamming. With a 14" airlock and adjustable material feed, it can handle any type of application. By incorporating side door access and slide out airlock, servicing the 9800 is easy and efficient. The 9800 comes standard with dual variable speed high velocity blowers. The safety cage top with hinged opening makes filling the hopper a safe and easy process.

Production Rates

Cellulose: 3300 lbs/hr
Fiberglass: 1400 lbs/hr
Rockwool: 1800 lbs/hr



Image of Blower Box



Powerful Dual Agitation



Product Safety Cage

Specifications

- Weight: 650 lbs
- Dimensions: 26" W x 48" L x 44"H
- Airlock: 14"
- Blower Size: Dual High Velocity
- 3" outlet port
- Hopper Capacity: 15 cubic feet

Features

- Modular component design
- Slide out airlock
- Side door access
- Welded steel construction with powder coat finish
- Hinged, grated hopper guard top
- 1.5 hp, single phase, farm duty drive motor

Options

- Single Input, 220v version
- Triple Input 110v version
- 50 hz and CE versions available
- Nickel-plated coating on airlock for fireproofing application