

# INSULGUARD® Heavy Duty™

## Description

Insulguard® Heavy Duty™ Insulation Support Fabric is the highest strength support fabric in the Insulguard® family. It's open web allows premium air flow and durability.

## Applications

Residential and Commercial Net & Blow Applications. Ceilings, Walls, and Attic Knee walls.

## Dimensions

96" , 108" , and 120" Widths

300' , 375' , 600' , and 750' Standard Lengths

Custom Sizes Available. Folded and Unfolded Rolls Available.

## Typical Physical Properties

The information presented herein, while not guaranteed, is to the best of our knowledge true and accurate. Except when agreed to in writing for specific conditions of use, no warranty or guarantee expressed or implied is made regarding the performance of any product, since the manner of use and handling are beyond our control. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent. This information reflects typical properties and should not be considered as specifications.

**Bond** Continuous Filament Polypropylene

**Color** White

**Weight** 45 GSM

**Tensile MD/CD** 115lb/in | 55lb/in

ASTM D5034

**Elongation MD/CD** 30% | 60%

ASTM D5034



**INSULGUARD**  
PREMIUM INSULATION FABRIC



*Order info*

Heavy Duty™

Insulguard®

orders@pciindgroup.com

Tel: 855-9-BUYPCI