



**ATTIC LADDER DIMENSIONS**

<b>LWP</b>		22½"x47"	25"x47"	22½"x54"	25"x54"	30"x54"	22½" x 54"	25"x54"	30"x54"	
<b>Manufacturer's part number</b>		66801	66802	66803	66804	66809	66853	66854	66855	
Ceiling height	H	7'5" - 8'11"			7'10" - 10'1"			8'8" - 10'8"		
Rough opening	AxB	22½"x47"	25"x47"	22½"x54"	25"x54"	30"x54"	22½"x54"	25"x54"	30"x54"	
Outside frame dimensions		22"x46¾"	24½"x46¾"	22"x53½"	24½"x53½"	29½"x53½"	22"x53½"	24½"x53½"	29½"x53½"	
Internal frame dimensions		20½"x44⅞"	23"x44 ⅞"	20 ½"x51¾"	23"x51¾"	28"x51¾"	20½"x51¾"	23"x51¾"	28"x51¾"	
Projection	R	64½"			72"			75"½"		
Landing space	C	57½"			64"			65"½"		
Folded ladder height	K								10¾"	
Board movement after opening	P								1¼"	
Frame height									5½"	
Approx. Weight (lbs)		59	60	67	70	75	71	74	79	

Step length	E	13 ¾"
Step width		3 ⅞"
Step thickness		⅞"
Distance between steps		9 ⅞"

Technical specification:  
**maximum loading: 300 lbs**  
**R-value: 5.9**  
**insulation thickness: 1 ⅞"**  
**hatch thickness: 1 ⅜"**

Available only in sizes given above.