



AIR CONDITIONER

10,000 BTU SLIDER CASEMENT WINDOW AC



FOLLOW ME
Portable remote control
thermostat feature for
total room coverage



WINDOW AC FEATURES

- Electronic controls
- Full range air direction control
- Temperature output range of 62°F–86°F (17°C–30°C)
- Auto, Sleep, Dry & Energy Saver modes
- Full function remote control
- 24 hour timer
- Window mounting kit
- Auto restart function
- Tilt-out filter access

CHOOSING

THE RIGHT SIZE AIR CONDITIONER FOR YOUR ROOM

1 MEASURE AREA OF THE ROOM

CALCULATE ROOM SIZE
room length x room width = sq. ft.

2 MATCH ROOM SIZE WITH CORRECT BTUs

ROOM SIZE (sq. ft.)	BTUs	
150	10' x 15'	5,000
250	15.5' x 16'	6,000
350	17.5' x 20'	8,000
450	18' x 25'	10,000
550	22' x 25'	12,000
700	25' x 28'	15,000
1,000	31.25' x 32'	18,000
1,500	37.5' x 40'	25,000
2,000	40' x 50'	28,500

3 CONFIRM WINDOW OPENING SIZE

MEASURE WINDOW OPENING IN INCHES
for thru-the-wall units,
confirm & measure wall opening size in inches

4 CHECK ELECTRICAL REQUIREMENTS

OUTLET CONFIGURATIONS

DETERMINE IF YOUR CIRCUIT IS ADEQUATE

3PASC10000	
UPC CODE	8-42149-02422-2
COOLING CAPACITY (BTU)	10,000
COVERAGE (sq. ft.)	400–450
EER	10.4
ENERGY STAR RATED	No
FAN SPEEDS (Cool/Fan)	3/3
AMPS	8.5
WATTS	961
DECIBELS (Hi/Mi/Lo)	61/58/56
WINDOW WIDTH (Min./Max.) (in.)	15 ^{1/2} /16 ^{1/3}
WINDOW HEIGHT (Min./Max.) (in.)	21 ^{1/3} / 39 ^{1/2}
UNIT DIMENSIONS (WxHxD) (in.)	14 ^{3/4} x 23 ^{1/2} x 21
PKG. DIMENSIONS (WxHxD) (in.)	18 ^{1/2} x 26 ^{3/4} x 23
STUFFING QTY. (20'/40'/40' HQ)	164/344/344
WEIGHT (Net/Gross) (lbs.)	77/89
REFRIGERATION	R410A
OUTLET CONFIGURATION	15 AMP 115V



PA/SS_3PASC10000/05022019

5401 Dansher Road
Countryside, IL 60525

866.996.9255
630.323.2301

www.perfectaire.us
support@perfectaire.us