

DATA SHEET

EcoRoll® Insulation

with ECOSE® Technology



DESCRIPTION

EcoRoll insulation is a cost-effective thermal and acoustical barrier for energy-efficient construction. EcoRoll insulation can be used in new and retrofit wood and metal frame applications in residential, commercial and manufactured housing structures.

APPLICATIONS

- Cavity walls, exterior and partition walls, floors, ceilings, attics, basements and crawlspaces

SPECIFICATION COMPLIANCE

- ASTM C665 (facing);
 - Type I, Class A, (Unfaced)
 - Type II, Class C, Category 1 (Kraft)
 - Type III, Class B, Category 1 (Foil)
- California Energy Commission
- MEA #498-90-M
- State of Minnesota

INDOOR AIR QUALITY

- UL Environment
 - GREENGUARD Certified
 - GREENGUARD Gold Certified
 - Validated to be Formaldehyde-Free
- EUCB Certified

CONTRACTOR: _____

JOB: _____

DATE: _____

DOING MORE FOR THE WORLD WE LIVE IN.

Knauf Insulation products with ECOSE® Technology are made using our patented, bio-based binder - a smarter alternative to the phenol/formaldehyde (PF) binder traditionally used in fiberglass products. The bio-based binder holds our product together, gives the product its unique appearance and makes it formaldehyde-free.

All of our products are made from sustainable resources, such as recycled glass and sand. And we're proud to be putting glass bottles back to work rather than into landfills. Our products are made with a minimum of 50% recycled glass—totaling an average of 26 million bottles each month.

with ECOSE®
TECHNOLOGY



TECHNICAL DATA

Property (Unit)	Test	Performance
Corrosion	ASTM C1617	Pass
Thermal Value	ASTM C518	See Forms Available chart
Water Vapor Permeance	ASTM E96	Kraft Faced: 1.0 perms or less, Foil Faced: 0.05 perms
Water Vapor Sorption (by weight)	ASTM C1104	Less than 5%
Combustibility	ASTM E136	Non-combustible (unfaced only)
Mold Growth	ASTM C1338	Pass
Surface Burning Characteristics (flame spread/smoke developed)	ASTM E84	Unfaced: 25/50, Kraft facing will burn and should not be left exposed

FORMS AVAILABLE

R-Value	Thickness	Unfaced - Width	Kraft - Width	Foil - Width
Retail Rolls				
R-11	3½" (89 mm)	15", 16", 23", 24" (381, 406 584, 610 mm)	15", 16", 23", 24" (381, 406 584, 610 mm)	15" (381 mm)
R-13	3½" (89 mm)	15", 24" (381, 610 mm)	15", 23" (381, 584 mm)	–
R-19	6¼" (159 mm)	12", 15", 23", 24" (305, 381, 584, 610 mm)	15", 16", 23", 24" (381, 406 584, 610 mm)	–
R-25	8½" (203 mm)	15", 23" (381, 584 mm)	16", 23" (406, 584 mm)	–
R-30	10" (254 mm)	23" (584 mm)	–	–
Manufactured Housing Rolls				
R-5	1½" (38 mm)	15" (381 mm)	–	–
R-7	2¼" (64 mm)	15", 16", 42", 48", 90", 96" (381, 406, 1067, 1219, 2286, 2438 mm)	–	–
R-11	3½" (89 mm)	15", 48", 72", 84", 90", 96" (381, 1219, 1829, 2134, 2286, 2438, mm)	15" (381 mm)	–
R-13	3½" (89 mm)	15" (381 mm)	15" (381 mm)	–
R-14	3½" (89 mm)	72" (1829 mm)	–	–
R-19	6¼" (159 mm)	15", 48", 92½" (381, 1219, 2,350 mm)	15", 23" (381, 584 mm)	–
R-22	7" (178 mm)	84" (2134 mm)	–	–
R-25	8½" (203 mm)	–	15" (381 mm)	–

**This table is meant as a quick reference guide as product availability varies by region.
Please check with your Territory Manager for a full product offering in your region.**


2012 International Energy Conservation Code Climate Zones

WALL INSULATION

Whenever exterior siding is removed on an:

- Uninsulated wood-frame wall:
 - Drill holes in the sheathing and blow insulation into the empty wall cavity before installing the new siding
- Zones 3–4:
 - Add R-5 insulative wall sheathing beneath the new siding.
- Zones 5–8:
 - Add R-5 to R-6 insulative wall sheathing beneath the new siding.
- Insulated wood frame wall, for Zones 4–8:
 - Add R-5 insulative sheathing before installing the new siding.

Reference: DOE/CE-0180 2008. Insulation Fact Sheet



NEW WOOD-FRAMED HOUSES						
Zone	Heating System	Attic	Cathedral Ceiling	Wall		Floor
				Cavity	Insulation Sheathing	
1	All	R-30 to R-49	R-22 to R-38	R-13 to R-15	None	R-13
2	Gas, oil, heat pump	R-30 to R-60	R-22 to R-38	R-13 to R-15	None	R-13, R-19, R-25
	Electric furnace					
3	Gas, oil, heat pump	R-30 to R-60	R-22 to R-38	R-13 to R-15	None	R-25
	Electric furnace				R-2.5 to R-5	
4	Gas, oil, heat pump	R-38 to R-60	R-30 to R-38	R-13 to R-15	R-2.5 to R-6	R-25 to R-30
	Electric furnace				R-5 to R-6	
5	Gas, oil, heat pump	R-38 to R-60	R-30 to R-38	R-13 to R-15	R-2.5 to R-6	R-25 to R-30
	Electric furnace		R-30 to R-60	R-13 to R-21	R-5 to R-6	
6	All	R-49 to R-60	R-30 to R-60	R-13 to R-21	R-5 to R-6	R-25 to R-30
7	All	R-49 to R-60	R-30 to R-60	R-13 to R-21	R-5 to R-6	R-25 to R-30
8	All	R-49 to R-60	R-30 to R-60	R-13 to R-21	R-5 to R-6	R-25 to R-30

EXISTING WOOD-FRAMED HOUSES			
Zone	Add Insulation to Attic		Floor
	Uninsulated Attic	Existing 3-4 Inches of Insulation	
1	R-30 to R-49	R-25 to R-30	R-13
2	R-30 to R-60	R-25 to R-38	R-13 to R-19
3	R-30 to R-60	R-25 to R-38	R-19 to R-25
4	R-30 to R-60	R-38	R-25 to R-30
5-8	R-49 to R-60	R-38 to R-49	R-25 to R-30

ACOUSTICAL PERFORMANCE

EcoRoll insulation provides excellent acoustical properties and will reduce sound transmission when properly installed in partition walls and acoustical ceiling and floor systems. Knauf acoustical/thermal insulation can improve STC ratings in wood stud construction by 3 to 5 points and metal stud construction by 8 to 10 points depending upon the complexity of the wall configurations, R-values and layers of insulation.

FIBERGLASS AND MOLD

Fiberglass insulation will not sustain mold growth. However, mold can grow on almost any material when it becomes wet and contaminated. Carefully inspect any insulation that has been exposed to water. If it shows any sign of mold, it must be discarded. If the material is wet, but shows no evidence of mold, it should be dried rapidly and thoroughly. If it shows signs of facing degradation from wetting, it should be replaced.

CERTIFICATIONS



Check with your Knauf Insulation Territory Manager to ensure information is current.

The chemical and physical properties of this product represent average values determined in accordance with accepted test methods. The data is subject to normal manufacturing variations. The data is supplied as a technical service and is subject to change without notice. References to numerical flame spread ratings are not intended to reflect hazards presented by these or any other materials under actual fire conditions.

This product is covered by one or more U.S. and/or other patents.
See patent www.knaufnorthamerica.com/patents

Visit knaufnorthamerica.com to learn more.

KNAUF INSULATION, INC.

One Knauf Drive
Shelbyville, IN 46176

Technical Support

(317) 398-4434 ext. 8727
info.us@knaufinsulation.com

02-20

© 2020 Knauf Insulation, Inc.