



HUNTER
CONTINUOUS INSULATION

Hunter Panels Xci

Packaging & Weight Chart

	FOAM	R-VALUE	PCS/PL	LBS/4X8 PC	LBS/4X8 PL	4X8 SF/PL	SF 48' TRL	WEIGHT PER SF
Xci FOIL	1.0	6.5	48	6.37	305.66	1536	36864	0.200
	1.5	10.0	32	9.02	288.77	1024	24576	0.280
	2.0	13.3	24	11.71	281.09	768	18432	0.370
	2.5	17.0	19	14.37	272.99	608	14592	0.450
	3.0	20.3	16	17.02	272.38	512	12288	0.530
	3.5	24.0	13	19.71	256.26	416	9984	0.620
	4.0	27.0	12	22.37	268.42	384	9216	0.700
Xci FOIL (CLASS A)	1.0	6.3	48	8.67	416.00	1536	36864	0.271
	1.5	9.5	32	12.99	416.00	1024	24576	0.406
	1.6	10.2	30	13.85	416.00	960	23040	0.433
	2.0	13.0	24	17.34	416.00	768	18432	0.542
	2.5	16.0	19	21.66	412.00	608	14592	0.677
	3.0	19.0	16	26.00	416.00	512	12288	0.813
	3.5	22.0	13	30.33	395.00	416	9984	0.948
	4.0	25.2	12	34.66	395.00	384	9216	1.083
Xci 286	1.0	6.3	48	8.67	416.00	1536	36864	0.271
	1.5	9.5	32	12.99	416.00	1024	24576	0.406
	1.6	10.2	30	13.85	416.00	960	23040	0.433
	2.0	13.0	24	17.34	416.00	768	18432	0.542
	2.5	16.0	19	21.66	412.00	608	14592	0.677
	3.0	19.0	16	26.00	416.00	512	12288	0.813
	3.5	22.0	13	30.33	395.00	416	9984	0.948
	4.0	25.2	12	34.66	395.00	384	9216	1.083
Xci CG	1.0	6.0	48	12.24	587.47	1536	36864	0.380
	1.5	9.0	32	15.03	480.90	1024	24576	0.470
	2.0	12.1	24	17.85	428.40	768	18432	0.560
	2.5	15.3	19	20.64	392.14	608	14592	0.640
	3.0	18.5	16	23.43	374.85	512	12288	0.730
	3.5	21.7	13	26.25	341.25	416	9984	0.820
	4.0	25.0	12	29.04	348.47	384	9216	0.910
Xci CG (CLASS A)	1.0	6.0	48	12.50	600.00	1536	36864	0.391
	1.5	9.0	32	15.35	491.20	1024	24576	0.480
	2.0	12.1	24	18.20	436.80	768	18432	0.569
	2.5	15.3	19	20.75	394.25	608	14592	0.648
	3.0	18.5	16	23.30	372.80	512	12288	0.728
	3.5	21.7	13	26.15	339.95	416	9984	0.817
	4.0	25.0	12	29.00	348.00	384	9216	0.906
Xci CONCAST	1.0	6.5	48	6.00	312.00	1536	36864	0.190
	1.5	10.0	32	8.00	279.00	1024	24576	0.250
	2.0	13.3	24	11.00	270.00	768	18432	0.340
	2.5	17.0	19	13.30	252.70	608	14592	0.420
	3.0	20.3	16	16.00	255.00	512	12288	0.500
	3.5	24.0	13	16.87	219.30	416	9984	0.527