

ROBIN HOOD'S BAY ERRATA

PAGE 48

Actual Chest (A on schematic):

92.5	103.5	114.5	125.5	136.5	cm
36 ½	40 ¾	45	49½	53¾	in

PAGE 50

... work short rows to shape the shoulders as follows:

Short row 1 (RS): K67 (72, 78, 79, 81), w&t.

Short row 2 (WS): P48 (52, 58, 59, 60), w&t.

Short row 3: K54 (59, 65, 66, 67) picking up wrap and working tog with wrapped st, w&t.

Short row 4: P60 (66, 72, 73, 74) picking up wrap and working tog with wrapped st, w&t.

Short row 5: K66 (73, 79, 80, 81) picking up wrap and working tog with wrapped st, w&t.

Short row 6: P72 (80, 86, 87, 88) picking up wrap and working tog with wrapped st, w&t.

Short row 7: ...

PAGE 51

Cont to inc 1 st at neck edge on RS rows taking the inc into moss st until you have 8 sts worked in moss st at neck edge side of cable. On next WS row, place a marker at each end of moss and cable panel (24 sts between markers).

Cont to inc 1 st at neck edge on RS rows taking the inc into St st and working moss and cable panel as set to 39 (42, 44, 45, 47) sts, ending with a WS row and AT THE SAME TIME...

PAGE 52

Cont to inc 1 st at neck edge on WS rows to 39 (42, 44, 45, 47) sts, ending with a WS row.

With RS facing, join the two front pieces as follows:

K to end, cast on 8 (8, 10, 9, 8) sts, work across left front keeping moss and cable patt correct. 86 (92, 98, 99, 102) sts

Now work straight as foll:

Row 1 (WS): K1, p to m, sm, work in patt as set to m, sm, p to last st, k1.

Row 2 (R S): K to m, sm, work in patt as set to m, sm, k to end.

Rep rows 1-2 until front measures 17 (16, 15.5, 15, 13.5)cm/6¾ (6¼, 6, 6, 5¼)" from arm selvedge of picked-up sts at saddle, ending with a WS row.

SHAPE ARMHOLE

Cont in patt as set and working the increases one st in from each side, inc 1 st at each end of next row and then foll 3rd (3rd, 3rd, 2nd, 2nd) row 1 (3, 4, 9, 12) times ending with a WS row. 90 (100, 108, 119, 128) sts

With RS facing, join the front and back pieces as foll:

Keeping moss and cable patt correct, work across front sts, cast on 10 (12, 16, 17, 20) sts for underarm, k across back sts, cast on 10 (12, 16, 17, 20) sts, k to m. This marker now marks beg of rnd. 200 (224, 248, 272, 296) sts
From this point onwards the body is worked in the rnd.

BODY

Cont in St st keeping the moss and cable patt correct (cables still made every 7th rnd), until body measures 35.5 (37, 38, 39.5, 40.5)cm/ 14 (14½, 15, 15½, 16)" from underarm cast on.

PAGE 53

n.b. Patt continues with the foll rib section (omit "Next rnd" and Sizes 1&5 only instructions on p52)

Change to 3.5mm circular ndl.

Rib rnd: Moss 8, p1, k2, p2, k2, p1, moss 8, sm, p1, *k2, p2; rep from * to last 3 sts, k2, p1.

Rep Rib rnd until rib measures 5cm/2".

Cast off loosely in rib.

SLEEVES

With RS of saddle facing, using 4mm circular needle, join yarn at right side of saddle (when working) and knit from stitch holder as follows: K1 (3, 2, 4, 4), k2tog, k3 (4, 4, 5, 3), k2tog, k3 (3, 3, 4, 3), [k2tog] 1 (0, 1, 0, 1) times, k1 (0, 2, 0, 3), pm (this will be mB), pick up and k30 (32, 32, 34, 35) sts down side of armhole to underarm cast-on point (approximately 1 st every 2 rows), pm (mC), pick up and k12 (14, 18, 20, 24) sts from underarm cast-on, pm (mD), pick up and k30 (32, 32, 34, 35) sts from other side of armhole to point at which yarn was joined, pm (mA). 83 (90, 96, 103, 110) sts

Shape upper sleeve cap with short rows as foll:

Short row 1 (RS): Slip mA, k to 1 st after mB, w&t.

Short row 2 (WS): P to mA, w&t first st after mA.

Short row 3: K to wrapped st, k wrapped st with its wrap, k1, take yarn back, w&t.

Short row 4: P to wrapped st, purl wrapped st with its wrap, p1, bring yarn to front, w&t.

Rep short rows 3-4 twice more – this skips 1 st between each w&t, easing the top of the shoulder cap into the side section.