



The next generation of innovative protective coatings

Liquid Rubber Color Waterproof Sealant is a brush, roll-on and spray-able high-performance, acrylic, elastomeric coating that can be applied over many existing surfaces including concrete, wood, brick, metal... which forms a durable, flexible, seamless, colored membrane.

Liquid Rubber Color Waterproof Sealant contains no solvents, is non-flammable and not affected by sunlight or occasional chemical spills.

Liquid Rubber Color Waterproof Sealant Performance Features

- Excellent solar reflectivity and emissivity
- UV resistance
- No VOC's or solvents
- Color options
- Handles intermittent hydrocarbon or chemical spills
- Reflective
- Highly Flexible w/ reduced stickiness
- Strong adhesion to concrete and mod-bit surfaces

Application Equipment

Liquid Rubber Color Waterproof Sealant is applied using a brush, roller or paint sprayer to provide a seamless and fully adhered membrane to most substrates. This highly flexible all-purpose sealant is designed as a stand-alone. Liquid Rubber Color Waterproof Sealant will cover 20 ft²/gal (0.5 m²/L) for 40 mils (1 mm).

Drying Time

At 25°C and 50% relative humidity, Liquid Rubber Color Waterproof Sealant fully cures in 24-48 hours. Curing time increases in colder temperatures or higher humidity so environmental conditions must be considered before application.

Suitable Applications include but are not limited to:

- RV Roofs (Primer may be required)
- Walls & Ceilings
- Roofs (Primer may be required)
- Secondary Containment of Hydrocarbons
- Concrete & Modified-Bitumen

Physical Properties

Color (Liquid)	Colors Available	Water Absorption (EN 1062)	0.007 kg/m ² -hr ^{0.5}
% solids (V/V) (Liquid)	48-52%	Accelerated Weathering	No degradation, 250 hrs
Tensile strength	>180 psi	Durometer Hardness	20-25 Shore A
Elongation	>1500%	Working Temp Range	-40°C to +150°C

The information contained herein is the best available to Liquid Rubber Canada Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Worldwide Inc. assumes no liability for any damages incurred in association with the use of Liquid Rubber Canada Inc. products. Information is subject to change without notice.

Limitations & Warranty

- Do not apply to dirty or contaminated surfaces
- Do not apply below 10°C
- Avoid contact with solvents and solvent type adhesives

Packaging

- 205 litre plastic drum (55 Gal)
- 18.9 litre pail (5 Gal)
- 3.78 litre can (1 Gal)