

Liquid Rubber MetalSafe Sealant™ is a single-component, liquid applied corrosion protective waterproofing sealant combining various elastomeric polymers for a high-performance, durable, seamless membrane.

Containing no solvents, Liquid Rubber MetalSafe Sealant™ is non-flammable and will not damage polyurethane or polystyrene insulation materials. A variety of different reinforcing fabrics can be imbedded into the membrane to produce superior waterproofing protection.

### Liquid Rubber MetalSafe Sealant™ Performance Features

- **Waterproof – low vapor permeability**
- **No VOC content**
- **No Solvents**
- **No harmful odors**
- **Freeze/thaw stable – stored at any temperature**
- **Excellent adhesion to the substrate so water will not run beneath the membrane**
- **Use directly over light rust**

### Application Equipment

Liquid Rubber MetalSafe Sealant™ is applied using a brush, roller or sprayer to provide a seamless and fully adhered membrane to most substrates. This all-purpose waterproofing sealant is designed for roof and concrete surfaces as well sealing cracks, joints and flashings.

### Drying Time

At 25°C and 50% relative humidity, Liquid Rubber MetalSafe Sealant™ fully cures in 24-48 hours. Curing time increases in colder temperatures or higher humidity so environmental conditions must be considered before application.

### Suitable Applications include but are not limited to:

- Metal Roof Maintenance & Restoration
- Beams & Pipes
- Tanks & Containment Areas
- Gutters & Eaves Through Repair
- Metal Planter Boxes
- Flashings & Vents

### Physical Properties

Color (Liquid)	Brown to Black	Water Absorption (EN 1062)	0.0002 kg/m <sup>2</sup> hr <sup>0.5</sup> (Excellent)
% solids (wt) (Liquid)	60 - 63%	Accelerated Weathering	No degradation 400 hrs UV
Tensile strength	>120 psi	Salt Fog ASTM B 117-97	1200 hrs Passed
Elongation	>950%	Freeze/Thaw Stability	Pass – 10 cycles
Low Temp Flex	-15C	Adhesion to Clean Steel	15 psi ASTM C-794

### Limitations & Warranty

- Do not apply to dirty or contaminated surfaces
- Do not apply below 5°C
- Avoid contact with solvents and solvent type adhesives
- Do not apply over coal tar

### Packaging

- 205 litre plastic drum (55 Gal)
- 18.9 L (5-Gal) Pails
- 3.78 L (1-Gal) Cans
- 946 ml (1 Quart) Cans

The information contained herein is the best available to Liquid Rubber Canada Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Canada Inc. assumes no liability for any damages incurred in association with the use of Liquid Rubber Canada Inc. products. Information is subject to change without notice.