

Liquid Rubber Multi-Purpose Primer is a high performance, engineered bonding aid designed to improve the adhesion of Liquid Rubber membranes and minimize moisture vapor drive over a variety of substrates. Liquid Rubber Multi-Purpose Primer is a single component epoxy composition suitable for easy and safe application to numerous surfaces including concrete, wood, and cures into a hard, clear film.

Liquid Rubber Multi-Purpose Primer Performance Features

- Low Moisture Vapor Drive
- Hard, Clear Finish
- High Coverage Rate
- Excellent Adhesion On Most Substrates

Application Equipment & Coverage

Liquid Rubber Multi-Purpose Primer is applied using a single component system using either by brush, roller or spray application. This primer will require one to two coats depending on the absorbent nature of the substrate, with the goal of minimizing vapor drive and maximizing adhesion of the waterproof membrane.

The recommended coating thickness of the Multi-Purpose Primer is between 4-5 mils DFT (.01 mm) (200-250 ft²/gal). For best results, the Multi-Purpose Primer should be applied to a dry surface that is free of dirt, debris, oil and grease. Application immediately before the onset of rain is not recommended.

Drying Time

Curing time will vary depending on temperature and relative humidity. The Multi-Purpose Primer will be dry to the touch in 10 minutes and will be ready for coating within 1-2 hours at 20°C (50% RH). Apply topcoat when the primer is tack free within 12 hours.

Suitable Applications include but are not limited to:

- Wood
- Modified-Bitumen
- HDPE & Concrete
- Metal

Physical Properties

Color (Liquid)	Clear
% solids (wt) (Liquid)	40%
Viscosity	50 CPs

Adhesion to Wood	Cohesive Failure
Adhesion to Concrete	Cohesive Failure
Adhesion to Wet Wood	Excellent

Limitations & Warranty

- Do not apply to dirty or contaminated surfaces
- Do not apply below 10°C
- Not suitable for extended UV exposure

Packaging

- 205 L plastic drum (55 Gal)
- 18.9 L pail (5 Gal)
- 3.78 L can (1 Gal)

The information contained herein is the best available to Liquid Rubber Canada Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Canada Inc. assumes no liability for any damages incurred in association with the use of Liquid Canada Inc. products. Information is subject to change without notice.