



The next generation of innovative protective coatings

Liquid Rubber RV Roof Coating is a brush, roll-on and spray-able high-performance, acrylic, elastomeric coating that can be applied over standard surfaces on recreational vehicle roofs including EPDM, fiberglass, wood and metal as a protective membrane.

Liquid Rubber RV Roof Coating contains no solvents, is non-flammable and not affected by sunlight or occasional chemical spills. The cured membrane is flexible with excellent UV resistance and solar reflectivity. Above all, the Liquid Rubber RV Roof Coating is waterproof and durable to provide the quality your RV deserves.

Liquid Rubber RV Roof Coating Performance Features

- Excellent UV Resistance and Solar Reflectivity
- No Solvents and VOC-Free
- Color options
- Strong adhesion to standard RV Roof Surfaces
- Highly Reflective
- Highly Flexible w/ reduced stickiness

Application Equipment

Liquid Rubber RV Roof Coating is applied using a brush, roller or paint sprayer to provide a seamless and fully adhered membrane to most substrates. This highly flexible all-purpose sealant is designed as a stand-alone coating or can be applied over EPDM/TPO Primer for hard to stick to surfaces. Liquid Rubber Rubber RV Roof Coating will cover approx 100 ft² per coat. Apply 2-3 coats minimum.

Drying Time

At 25°C and 50% relative humidity, Liquid Rubber RV Roof Coating fully cures in 24-48 hours. Curing time increases in colder temperatures or higher humidity so environmental conditions must be considered before application.

Suitable Applications include but are not limited to:

- RV Roofs
- Walls & Ceilings
- Secondary Containment of Hydrocarbons
- RV Roofs, Concrete & Modified-Bitumen Roofs

Physical Properties

Color (Liquid)	Colors Available	Water Absorption (EN 1062)	0.007 kg/m ² -hr ^{0.5}
% solids (V/V) (Liquid)	48-52%	Accelerated Weathering	No degradation, 250 hrs
Tensile strength	>180 psi	Durometer Hardness	20-25 Shore A
Elongation	>1500%	Working Temp Range	-40°C to +150°C

Limitations & Warranty

- Do not apply to dirty or contaminated surfaces
- Do not apply below 10°C
- Avoid contact with solvents and solvent type adhesives

Packaging

- 205 litre plastic drum (55 Gal)
- 18.9 litre pail (5 Gal)
- 3.78 litre can (1 Gal)

The information contained herein is the best available to Liquid Rubber Canada Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Worldwide Inc. assumes no liability for any damages incurred in association with the use of Liquid Rubber Canada Inc. products. Information is subject to change without notice.