



The next generation of innovative protective coatings

Liquid Rubber RV Roof Coating is a polyurethane based, elastomeric coating that can be applied over standard surfaces on recreational vehicle roofs including EPDM, fiberglass, wood and metal, as a protective waterproof membrane.

Liquid Rubber RV Roof Coating contains no solvents, is non-flammable and is not affected by sunlight or mild cleaning chemicals. The cured membrane is highly flexible with excellent UV resistance and solar reflectivity. Above all, Liquid Rubber RV Roof Coating is waterproof and durable to provide the quality your RV deserves.

Liquid Rubber RV Roof Coating Performance Features

- Excellent Durability
- Ultra-Low VOC
- Tack Free Finish
- Strong Adhesion to Standard RV Roof Surfaces
- Highly Reflective
- Highly Flexible

Application Equipment

Liquid Rubber RV Roof Coating is applied using a brush, roller or airless paint sprayer to provide a seamless and fully adhered membrane to most substrates. This highly flexible sealant is designed to be used with our Seam Tape and applied over our Multi-Purpose Primer or EPDM Primer depending on the surface. Liquid Rubber RV Roof Coating will cover approx. 50 ft² per gallon (final coverage). Apply a minimum of 2 coats.

Drying Time

At 25°C and 50% relative humidity, Liquid Rubber RV Roof Coating should be dry to the touch after 6 hours and fully cures in 48 hours. Curing time increases in colder temperatures or higher humidity so environmental conditions must be considered before application.

Suitable Applications include but are not limited to:

- RV Roofs
- EPDM, Metal
- Concrete Roofs
- PVC, Fiberglass

Physical Properties

Color (Liquid)	White
% solids (V/V) (Liquid)	46% by volume
Tensile strength	980 psi
Elongation	400%

Water Absorption (EN 1062)	0.003 kg/m ² hr0.5
Adhesion to Metal	Cohesive Failure
Durometer Hardness 00	75
Working Temp Range	-40°C to +80°C

Limitations & Warranty

- Do not apply to dirty or contaminated surfaces
- Do not apply below 10°C / 50°F
- Avoid contact with solvents and solvent type adhesives

Packaging

- 205 L plastic drum (55 Gal)
- 18.9 L pail (5 Gal)
- 3.78 L can (1 Gal)

The information contained herein is the best available to Liquid Rubber Canada Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Worldwide Inc. assumes no liability for any damages incurred in association with the use of Liquid Rubber Canada Inc. products. Information is subject to change without notice.