

Liquid Rubber NeoPond Sealant

Liquid Rubber NeoPond Sealant is the ultimate pond coating. This well-balanced formulation is designed for UV stability, durability, elasticity, and excellent bond to most substrates. It is also fish and plant safe and comes in a variety of colors. Liquid Rubber NeoPond Sealant is easy to apply using a brush, roller, or airless paint sprayer. Anyone can do it!

Liquid Rubber NeoPond Performance Features

- Provides a superior waterproofing membrane
- Ultra-Low VOC's & no solvents
- Cleans up with soap and water

- Fish and Plant safe
- Easy application
- Water-based

Application Equipment

We recommend applying this product with a paint brush, 3/8 (10mm) paint roller or appropriate airless paint sprayer.

Drying time

Allow the Liquid Rubber NeoPond Sealant to dry, approximately 4-6 hours, until dry to the touch with nothing wet underneath and it is uniform in color. Allow for 3-5 days (minimum) before filling.

Suitable Applications include

 Concrete, wood, EPDM pond liners (with the use of our EPDM primer or Multi-Purpose Primer).

Limitations & Warranty

- Do not apply to dirty, greasy or contaminated surfaces
- Do not apply below 10°C
- Use with Liquid Rubber Multi-Purpose Primer
- Use with Liquid Rubber Geo-Textile
- Avoid contact with solvents and solvent type adhesives

Ask your local Liquid Rubber representative about other substrates.

Packaging

Liquid Rubber Neoprene Pond Sealant is available in:

- 3.78 L can (1 Gal)
- 18.9 L pail (5 Gal)

The information contained herein is the best available to Liquid Rubber Canada Inc. and its affiliated companies relating to Liquid Rubber products and the use of Liquid Rubber products. It is based on tests believed to be reliable. There is no warranty expressed or implied in association with product use. Liquid Rubber Canada Inc. assumes no liability for any damages incurred in association with the use of Liquid Rubber Canada Inc. products. Information is subject to change without notice.