

ON-ROAD

R-6101 Rooftop

Air Conditioner Unit

COMMERCIAL TRUCKS •
CONSTRUCTION • AGRICULTURE



The R-6101 is a lightweight, high-capacity unit with a styled low profile.

Our engineers set out to create a sleek, low profile housing that would look right at home on today's truck and heavy-equipment cabs. The injection-molded housing has pockets to hold the receiver drier, blower assembly, and evaporator core, so they're simpler to replace. A 12-inch Spal fan, dual-scroll/dual-inlet Spal blower, rifled-tube evaporator and a parallel flow condenser contribute to the improved performance.



Low profile ceiling plenum blends with any interior.

HEATER-A/C

R-6100 SPECIFICATIONS

BTUs	Cooling – 21,300 BTU @ 100°F (6.2kw @ 37.8°C) air temperature rise
AIR FLOW	299 CFM (508 m3/h)
WEIGHT	40lbs (18.1kg)
CURRENT	25.7 amps @ 13.6 VDC
DRAW	12.9 amps @ 27.2 VDC
CONTROLS	Three speed blower

R-6100 SYSTEM ORDERING GUIDE

	R-134a	NOTES
UNITS	R-6101-0P R-6101-0-24P	12 VDC 24 VDC
CONDENSER	Contained in R-6100 unit	
INSTALLATION KIT	78R1505 78R1077	Refrigerant hose and fittings, etc. * Rooftop condenser **
OPTIONS	Universal Roof Mount Kit Replacement Recirc. Filter Replacement Receiver Drier Replacement Plenum	RD-2-1302-0P *** 78R5300 74R2546 RD-2-5974-0P
COMPRESSOR	Requires compressor and mounting kit See Compressor Section	

* ATCO version

** EZ Clip version

*** Relocates unit mounting bolts to pick up integral roof bracing

