SUITABLE APPLICATIONS

Stadium Seating, Contract Interiors, Hotel/Motel Room Seating, Medical Office Seating, Restaurants, Residential, Office, Theater, Bus Seating, Interior or Exterior Use Recommended.

MAIN PROPERTIES

Flame Retardancy:

Manufactured to meet MVSS 302, California Tech Bulletin 117, IMO A.652(16)8.2, NFPA 260

Abrasion Resistance:

Protected with Prevent Topcoat to pass 250,000 Double Rubs Wyzenbeek/CFFA-1 Federal Standard 191A Method 5304

UV Light Resistance:

Protected with Prevent topcoat to achieve 1000 hours of Ultraviolet Resistance.

Bacterial Resistance:

Passes AATCC Test Method 147-1988 Bacteria Passes ASTM 1428 Pink Stain Passes ASTM G21 Mold Heat Sealable

Top Coated Lacquered with Prevent Topcoat for advanced protection and cleanability

TYPICAL VALUES FOR PHYSICAL PROPERTIES

WEIGHT	Oz/LnYD	25
THICKNESS	GA	50
WIDTH	Inches	54
TENSIL STRENGTH (ASTM D-751)	Lbs/Inch	65/65
TEAR STRENGTH (MF-MH BN 22.1)	LBS	15/7
COLD CRACK (MF-MH BN 128.01)	°F	-10
BACKING	6.5 oz 100% Knitted Polyester	

CLEANING AND MAINTENANCE

Most household soil can be easily removed with warm soapy water and several clear water rinses. Moderate scrubbing with a medium bristle brush will help to loosen the soiling agent from the impressions of the surface. For more specific staining, refer to the following guide.

STAIN	CLEANING INSTRUCTION
Soil, Eye shadow, Crayon, Chocolate, Suntan Lotion	Warm soapy water and rinse mild household cleanser such as 409® Rinse with clear water and dry.
Ball Point Ink	Immediately wipe with 70% rubbing alcohol. Rinse and dry with clean cloth. Rinse with clear water and dry.
Tar/Asphalt, shoe polish, grease	Remove immediately. Dampen cloth with mineral spirits, rub gently from outside edge of stain to center. Rinse with mild soap and water. Rinse with clear water and dry.
Surface Mildew	Use a mild household cleanser such as 409®. Rinse with clear water and dry. If mildew stain persists clean with 5:1 bleach and water. Rinse with clear water and dry.

Limited Warranty: One year limited Warranty