

Specification Sheet



- Slip resistant multi-directional patterned surface
- Heavy Duty Rubber Flooring with Smart & Non Slip Pattern
- Non Slip durable rubber floor
- Impression finish anti-creep reverse
- Good floor to foot cold insulation properties

PHYSICAL PROPERTIES

COLOUR:	BLACK	
ELASTOMER:	CHECKER PLATE	
HARDNESS SHORE A+5	65	ISO7619-1
SG (g/cm³):	1.5	ISO2781
TENSILE:	3.5	ISO37
ELONGATION %:	300	ISO37
COMPRESSION %:	43	ISO37
TEAR STRENGTH:		ISO34-1
ABRASION MM3:		ISO37
TEMPERATURE FROM (DEG C)	-20	
TEMPERATURE TO (DEG C)	70	

THICKNESSES

0.5– 1mm	+/- 0.2mm
1.5mm –3mm	+/- 0.3mm
4mm—5mm	+/- 0.4mm
6mm	+/- 0.5mm
8mm	+/- 0.7mm
10mm—15mm	+/- 1mm
20mm	+/- 1.4mm
25mm	+/- 1.75mm

ROLL TOLERANCES

Width tolerance:	+/- 2%	ISO 3302 SW1
Length tolerance:	+/- 2%	ISO 3302 SW1

QUALITY ASSURED PRODUCTS WITH FULL TRACEABILITY

Care should be taken in selecting the most suitable quality for each application. Advice is available but final responsibility remains with the customer.