



**EMERGENCY OVERVIEW:** Aerosol can intended to be used as a spray.  
Caution: Contents under pressure.  
Do not store at temperatures above 50° C(120° F)  
Do not puncture or incinerate.  
Avoid fire, flame and other sources of ignition  
Flammable aerosol.

**POTENTIAL HEALTH EFFECTS:**

Routes of exposure:

**INHALATION:** High vapour concentrations may cause drowsiness.  
Mild irritation to the nose, throat and respiratory tract.

**SKIN CONTACT:** Minor irritation to skin.

**EYE CONTACT:** Minor irritation to eyes.

**INGESTION:** May cause abdominal discomfort.

**OTHER HEALTH EFFECTS:** None known

<b>SECTION 4:</b>	<b>FIRST AID MEASURES</b>
-------------------	---------------------------

**INHALATION:** Move victim to fresh air. If irritation symptoms persist, get medical attention. If breathing has stopped, a trained person should perform an artificial respiration, otherwise get medical attention.

**SKIN CONTACT:** Wash off with soap and water. If irritation persists get medical attention.

**EYE CONTACT:** Immediately flush with water for fifteen minutes. If irritation persists get medical attention.

**INGESTION:** If swallowed do not induce vomiting. If conscious drink 1-2 glasses of water or milk. If vomiting occurs naturally, have victim lean forward to avoid aspiration. Otherwise get medical attention.

<b>SECTION 5: FIRE FIGHTING MEASURES</b>
--

FLASH POINT : <-73 °C  
Propellant only

Method used Tag closed cup  
 X  Estimated

FLAMMABLE LIMITS IN AIR (% by Volume)  
LOWER : 1.8 - 2.2  
UPPER : 8.4 - 9.5

AUTO IGNITION TEMPERATURE : N/A °C

EXTINGUISHING MEDIA : Dry chemical, CO2, Foam, water.

SPECIAL FIRE FIGHTING : Water from fogging nozzles may be used to cool closed containers  
PROCEDURE to prevent pressure build up if exposed to extreme temperatures.  
Treat as NFPA (National Fire Protection Association) Level 2 aerosol.

UNUSUAL FIRE AND : Container may explode if exposed to temperatures > 50° C (120° F)  
EXPLOSION HAZARDS : Sensitive to shock  
Sensitive to static discharge.

FLAMMABILITY OF AN AEROSOL IS DETERMINED BY FLAME PROJECTION:  
THE FLAME PROJECTION OF THIS PRODUCT IS CLASSIFIED AS:

- ZERO cm (NON-FLAMMABLE)
- 0 - 15 cm (CAUTION)
- 15- 45 cm (WARNING)
- OVER 45 cm (DANGER)

HAZARDOUS COMBUSTION PRODUCTS : Hydrocarbon fumes and smoke, CO where combustion is incomplete.

<b>SECTION 6 : ACCIDENTAL RELEASE MEASURES</b>
--

CONTAINMENT AND : Since this product is a sealed aerosol, accidental discharge of contents is unlikely  
CLEAN UP PROCEDURES: unless the can is punctured . Should this occur, eliminate all sources of ignition.  
Dike and contain the free liquid and absorb on vermiculite or spill pillows.  
Use inert absorbent material.

PERSONAL PROTECTIVE : Plastic or rubber gloves, apron may be required for clean up of large spills.  
EQUIPMENT: Respiratory protection may need to be utilized, depending upon the size of the spill.

<b>SECTION 7 :</b>	<b>HANDLING AND STORAGE</b>
--------------------	-----------------------------

**HANDLING:** Flammable aerosol  
Do not use near heat, fire, flame and other sources of ignition.  
Contents under pressure.  
Do not puncture or incinerate.  
Avoid spraying in the eyes.

**STORAGE:** Store in well ventilated area.  
Do not store at temperatures above 50° C(120° F)  
Do not store near heat, fire, flame and other sources of ignition  
Protect against physical damage

<b>SECTION 8 :</b>	<b>EXPOSURE CONTROL/PERSONAL PROTECTION</b>
--------------------	---

**ENGINEERING CONTROLS:** None required for product use.  
For handling large quantities of the product,  
such as in the manufacturing or warehouse, ventilation should be utilized.  
Testing of aerosol cans should be performed with explosion-proof  
ventilation equipment.

**VENTILATION:** Local exhaust ventilation is not required for product use.  
Use mechanical exhaust when ever is used indoors or on a continuous basis.

**RESPIRATORY PROTECTION:** None required for product use.  
For manufacturing of the product, respiratory protection may be considered.  
Ensure that the respirator meets current local Occupational Health and Safety  
Standards. Organic cartridges should be utilized with filtering respiratory  
protection.

**EYE PROTECTION:** None required for product use.  
For handling large quantities of the product,  
such as in the manufacturing or warehouse, safety glasses /goggles  
are recommended.

**SKIN PROTECTION:** None required for product use.  
For handling large quantities of the product,  
such as in the manufacturing or warehouse, plastic or rubber gloves  
are recommended.

**EXPOSURE LIMITS:** OSHA PEL-TWA: 1000 ppm Isobutane/Propane  
NTP : 1000 ppm Isobutane/Propane  
ACGIH TLV-TWA : 1000 ppm Isobutane/Propane  
IARC : 1000 ppm Isobutane/Propane  
NIOSH REL : 1000 ppm Isobutane/Propane

PRODUCT NAME: Footlogix Medical (020-491)  
SDS

PAGE 5 OF 8

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

THE FOLLOWING PHYSICAL DATA ARE APPROXIMATE ONLY AND DO NOT REPRESENT SPECIFICATION VALUES.THEY SHOULD ONLY BE USED IN THE CONTEXT OF THIS MATERIAL SAFETY DATA SHEET

APPEARANCE AND ODOUR : Aerosol can dispensing as a foam  
PHYSICAL STATE : Mixture of Liquids, Hazy creamy white  
BOILING POINT (°C) : N/A °C  
MELTING POINT(°C) : N/A °C  
FREEZING POINT(°C) : 0 °C  
VAPOUR PRESSURE (psig at 21 °C) : 40 -60 psig  
VAPOUR DENSITY (AIR=1) : > 1  
SPECIFIC GRAVITY (WATER=1) : .960- 1.030  
EVAPORATION RATE(n-BUTYL ACETATE=1) : <1  
pH : 7.2 – 8.2

**SECTION 10: STABILITY AND REACTIVITY**

STABILITY : Stable under normal conditions.  
HAZARDOUS POLYMERIZATION : Will not occur.  
CONDITIONS TO AVOID : Heat, fire, flame and other sources of ignition.  
MATERIALS TO AVOID : Strong oxidizers. Alkali materials and their hydroxides.  
HAZARDOUS DECOMPOSITION OR COMBUSTION PRODUCTS : Hydrocarbon fumes and smoke, CO where combustion is incomplete.

**SECTION 11 : TOXICOLOGICAL INFORMATION**

ACUTE EXPOSURE:

EFFECTS OF OVEREXPOSURE: Dizziness, nausea, irritation to skin and eyes.

<u>INGREDIENT</u>	<u>LD50(Oral,Rat)</u>	<u>LD50(Dermal, Rabbit)</u>	<u>LC50(Inhal. Rat, 4hr)</u>
-------------------	-----------------------	-----------------------------	------------------------------

Urea 46% Uncoated Prills	57-13-6	5-15	Oral LD50 - ranges from 8.5 g/kg (rat) to 28.5 g/kg (sheep)
Alcohol Ethyl 200 Proof	64-17-5	<1	TLV: 1000 ppm; 1880 mg/m <sup>3</sup> (as TWA) (ACGIH 1993-1994).

PRODUCT NAME: Footlogix Medical (020-491)  
SDS

PAGE 6 OF 8

PROPELLANT(S): N/A

Isobutane	75-28-5	1-10	TLV 1000 ppm
Propane	74-98-6	.5 – 5	TLV 1000 ppm

**CHRONIC EXPOSURE:**

CARCINOGENICITY OF PRODUCT : No adverse carcinogenic effects are anticipated

REPRODUCTIVE EFFECTS : No adverse reproductive effects are anticipated

TERATOGENICITY : No adverse teratogenic effects are anticipated

MUTAGENICITY : No adverse mutagenic effects are anticipated

SYNERGISTIC PRODUCTS : None known

SENSITIZATION TO:   RESPIRATORY TRACT: Mild irritation to the nose, throat .  
                          SKIN CONTACT:       Minor irritation to skin.  
                          EYE CONTACT:        Minor irritation to eyes.  
                          INGESTION:            May cause abdominal discomfort

<b>SECTION 12 :            ECOLOGICAL INFORMATION</b>
---

ECOTOXICITY :               None known

ENVIRONMENTAL FATE:       All precautions should be taken to prevent contact with the environment.  
                                  Spills and leaks should be immediately cleaned up and removed.  
                                  Do not contaminate domestic or irrigation water supplies, lakes, streams,  
                                  ponds, or rivers.

<b>SECTION 13:            DISPOSAL CONSIDERATIONS</b>
---

WASTE DISPOSAL METHOD     : Apply all Federal, Provincial, Municipal, State laws and Regulations  
                                  regarding disposal.

HOUSEHOLD DISPOSAL METHOD: User may discard empty container after flaring off vapours at safe a location, then place in recycle trash ONLY where such programs exist.

**SECTION 14 : TRANSPORTATION INFORMATION**

**NORTH AMERICA**

**CANADIAN TDG ACT SHIPPING DESCRIPTION:**

**US DOT CLASSIFICATION (49CFR 172.101,172.102)**

**GROUND:** ORM-D ; Consumer commodity.

**IN CONSUMER PACKAGING**

**SHIPPING NAME:** Aerosol  
**HAZARD CLASS :** 2.1 Flammable aerosol  
**ID NUMBER:** UN 1950  
**PACKAGE CERTIFICATION CODE:** LTD. QTY.



**TRANSPORT VIA WATER(IMDG):**

**IN CONSUMER PACKAGING:** Limited Quantity  
**SHIPPING NAME:** Aerosol  
**HAZARD CLASS :** 2.1 Flammable aerosol  
**ID NUMBER:** UN 1950  
**PACKAGE CERTIFICATION CODE:** LTD. QTY.



**TRANSPORT VIA AIR(IATA):**

**IN CONSUMER PACKAGING :** Limited Quantity  
**SHIPPING NAME:** Aerosol  
**HAZARD CLASS :** 2.1 Flammable aerosol  
**ID NUMBER:** UN 1950  
**PACKAGE CERTIFICATION CODE:** Y203 LTD. QTY.



**SECTION 15: REGULATORY INFORMATION**

**CANADA:**

**WHMIS CLASSIFICATION :** A, D-2B, B-5 Flammable Aerosol

**HMIS USA :** Health 1, Flammability 4, Reactivity 1

**UN 1950 :** Flammable Aerosol

**SECTION 16: OTHER INFORMATION**

**PREPARED BY :** MICHAEL GOMES  
**PRODUCT NAME:** Footlogix Pediceuticals DD Cream Mousse (020-491)  
**PAGE 8 OF 8**  
**SDS**

DATE OF PREPARATION: April 8<sup>th</sup>, 2015

---

THE INFORMATION CONTAINED IN THIS FORM IS BASED ON DATA FROM SOURCES CONSIDERED TECHNICALLY RELIABLE AND HAS BEEN PREPARED IN GOOD FAITH IN ACCORDANCE WITH THE AVAILABLE MATERIAL. IT IS PROVIDED AS A SERVICE TO THE PERSONS USING THE PRODUCT BUT CONDITIONS OF USE AND HANDLING MAY INVOLVE OTHER AND ADDITIONAL CONSIDERATIONS BEYOND THE CONTROL OF KVG GROUP INC.

NO WARRANTY, EXPRESSED OR IMPLIED, IS MADE AND KVG GROUP INC. WILL NOT BE LIABLE FOR ANY DAMAGES, LOSSES, INJURIES OR CONSEQUENTIAL DAMAGES WHICH MAY RESULT FROM THE USE OF RELIANCE ON ANY INFORMATION CONTAINED IN THIS FORM.