

MATERIAL SAFETY DATA SHEET

SECTION I Chemical Product and Company Identification

Trade Name Appearing on Label: **ORLY Prime Time** Chemical Family: Toiletries

Manufacturer/Distributor/Importers: Orly International, Inc.
 7710 Haskell Ave
 Van Nuys, CA 91406
 Prepared By: Dan Werner
 Date Prepared: 7-26-2010
 Updated: 12/26/13

Emergency Phone: (800) 424-9300
 Business Phone: (818) 994-1001

Poison Control Center - CHEMTREC: (800) 424-9300
 Poison Control Center - CHEMTREC International: (703)527-3887

SECTION II Potentially Hazardous Ingredients

Chemical Identity	%	CAS Number	OSHA (PEL)	Exposure Limits in Air	
				ACGIH (TLV)	Other
Isopropyl Alcohol	90 - 95%	67-63-0	400 ppm	400 ppm	
Diacetone Alcohol	5 - 10%	123-42-2	75 ppm	75 ppm	

SECTION III Hazard Identification

HMIS Rating Scale: 0 = Minimal 1 = Slight 2 = Moderate 4 = Severe

This Products Rating: Health: 2 Flammability: 3 Reactivity: 0

Material Appearance: Clear Liquid

Primary Route of Entry: Inhalation X Skin X Ingestion X

Ingredient(s) Listed as Cancer Causing Agents?:

NTP - no LARC Monographs - no OSHA - no

Target Organs Affected: kidneys, liver, skin, central nervous system

Short Term Effects:

Inhalation: may cause dizziness, drowsiness, headache and may affect the respiratory system and mucous membranes if inhaled for a prolonged time

Eyes: may cause stinging and irritation if product gets into open eyes.

Skin: may cause skin irritation if exposed repeatedly and over a prolonged period of time.

Signs and Symptoms of Over-Exposure: may cause dizziness

Medical Conditions Generally Aggravated by Exposure: none known

SECTION IV**First Aid Measures**

Eye Contact: Flush eyes with large amounts of warm water.

Skin Contact: Wash with soap and water.

Inhalation: If dizziness occurs, remove person to fresh air. If not breathing, give artificial respiration. Get Medical Attention immediately if not breathing.

Ingestion: Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Get immediate medical attention if symptoms appear.

SECTION V**Fire Fighting Measures**

Note: Explosive in presence of open flames and sparks, of heat.

Flash Point:11.6C (53F) - 12.7C (55F)

Flammable Limits in Air % - Lower: 2%, Upper: 12.7%

Extinguishing Media: Water Spray X Dry Chemical _
Carbon Dioxide _ Foam _

Fire Fighting Procedure: Small Fire: Use DRY chemical powder. LARGE fire: Use Alcohol foam, water spray or fog.

SECTION VI**Accidental Release Measures**

Spill & Leak Procedures: Collect with absorbent material and place into trash container.
Keep away from sources of ignition.

SECTION VII**Handling and Storage**

Handling: Provide exhaust ventilation or other engineering controls to remove the vapors.
Avoid contact with eyes. Wear suitable protective clothing.

Storage: Store at room temperature in a well ventilated area. Keep containers closed when not in use. Avoid all sources of ignition (spark or flame)

SECTION VIII**Exposure Controls and Personal Protection**

Use in a well ventilated area. Suggested protective clothing includes: Gloves, splash goggles or eye protection.

SECTION IX Physical and Chemical Properties

Water Solubility: Nil	Specific Gravity: (H ₂ O = 1): 0.785
Appearance: Clear Liquid	Boiling Range: 82.5C (180.5F)
%/Wt. Volatiles: 97 - 99.5 %	Melting Point: -88.5C (-127.3F)
pH: N/A	Vapor Pressure (mm Hg): 4.4 kPa @20C
Odor: Alcohol odor with an acetone-like odor	Vapor Density: 2.07 (Air = 1)
	Evaporation Rate: N/A
	Flashpoint: Closed Cup: 11.6C (53F) - 12.78C (55F)

SECTION X Stability and Reactivity

Chemical Stability: This product is stable under the recommended storage conditions.

Conditions to avoid: Storage in temperatures above 35 C.

Contact with Materials to avoid: n/a

Hazardous Decomposition Products: will not occur

Hazardous Polymerization: will not occur.

SECTION XI Toxicological Information

The product contains organic solvents that may cause non-allergic dermatitis from repeated prolonged contact with the skin. Vapors from the solvent may negatively affect the renal system, cause problems to the central nervous system and irritate the respiratory tracts.

Ingestion:	Hazardous in case of ingestion or inhalation.
Eyes:	This product may be a temporary eye irritant if it gets into the open eye.
Dermal:	May cause dry skin if exposed repeatedly and over a prolonged time.
Inhalation	Breathing small amounts during routine handling is unlikely to cause harmful effects. Breathing large amounts may be harmful and may cause headache, dizziness, drowsiness and difficulty breathing.
Overexposure:	
Chronic Effects:	Repeated or prolonged exposure to the substance can produce target organs damage.
Carcinogenicity:	Not listed as a carcinogen by IARC, NTP, OSHA, or ACGIH
Target Organs:	kidneys, liver, skin, central nervous system

SECTION XII Ecological Information

Ecotoxicity No information available

SECTION XIII Disposal Considerations

Waste Disposal: Dispose of absorbed material in accordance with local, state and federal regulations.

SECTION XIV **Transport Information**

Road Transport:

Class: 3
 Packaging Group: II
 Label: Paint
 UN Number: 1263

Maritime Transport:

Class: 3
 Packaging Group: II
 Label: Paint
 UN Number: 1263
 Marine Pollutant: No

Air Transport:

Class: 9
 Packaging Group: II
 Packaging instr.: 910 (Passenger)
 Label: Paint
 UN Number: ID8000

SECTION XV **Regulatory Information**

Labeling according to EEC-Directives.

Symbol: F

Indication of Danger: Highly flammable

EU Risk Phrases: R10 Flammable, R11 Highly Flammable, R20 Harmful by inhalation, R36 Irritating to the eyes, R67 Vapors may cause drowsiness and dizziness.

Safety Phrases: S16 Keep away from sources of ignition, No smoking, S23 Do not breathe vapors, S25 Avoid contact with eyes, S29 Do not empty into drains, S33 Take precautionary measures against static discharge.

Hazard Symbols: F - Highly Flammable

SECTION XVI **Other Information**

IMPORTANT NOTICE: The information presented herein is based on experimental data submitted by the manufacturers of the raw materials and is considered scientifically correct, however, no warrant or representation, express or implied, is made as to the accuracy or suitability of this information for application to the purchaser's intended purpose or for consequences of its use. Use these materials only as directed. If you have any questions regarding the proper interoperation of this sheet or the meaning of any terms used, we strongly urge you to speak with your physician. For further information concerning product safety and proper use, call the number listed on the front of the MSDS.

They Must be Used with Adequate Ventilation and in Accordance with Manufacturers Instructions.

Abbreviations Used:

NE = Not Established

NKn = Not Known

n/a = Not Applicable

C = Ceiling Limit

TS = Trade Secret

EST = Estimated

N/DA = No Data Available

NTP = National Toxicology Program

IRAC = International Agency for Research on Cancer

CHEMTREC = Chemical Transportation Emergency Center

OSHA = Occupational Safety and Health Administration

IPA = Isopropyl Alcohol (Rubbing Alcohol)

mm Hg = Millimeters of Mercury

PEL = Permissible Exposure Limit

TLV = Threshold Limit Value

STEL = Short Term Exposure Limit

NEGL = Negligible

NF = None Found

CAS = Chemical Abstract Service Number

NR = Not Required