



Safety Data Sheet

Issue Date: 18-Feb-2015

Revision Date: 27-Feb-2015

Version 1

1. IDENTIFICATION

Product Identifier

Product Name Shizaaam!

Other means of identification

SDS # YN-023CCCC

Recommended use of the chemical and restrictions on use

Recommended Use Nail lacquer.

Details of the supplier of the safety data sheet

Supplier Address

Young Nails Inc.
1149 North Patt St.
Bldg B
Anaheim, CA 92801

Emergency Telephone Number

Company Phone Number 714-992-1400
Emergency Telephone (24 hr) INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance According to product specification

Physical State Liquid

Classification

Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Serious eye damage/eye irritation	Category 1
Specific target organ toxicity (single exposure)	Category 3
Flammable Liquids	Category 2

Hazards Not Otherwise Classified (HNOC)

May be harmful if swallowed
Causes mild skin irritation

Signal Word

Danger

Hazard Statements

Harmful if inhaled
Causes serious eye damage
May cause drowsiness or dizziness
Highly flammable liquid and vapor

**Precautionary Statements - Prevention**

Use personal protective equipment as required
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Keep away from heat/sparks/open flames/hot surfaces. — No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof equipment
 Use only non-sparking tools
 Take precautionary measures against static discharge
 Keep cool

Precautionary Statements - Response

If exposed or concerned: Get medical advice/attention
 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 Immediately call a poison center or doctor/physician
 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 Call a POISON CENTER or doctor/physician
 IN CASE OF FIRE: Use CO₂, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up
 Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS No	Weight-%
Ethylacetate	141-78-6	5-55
n-Butyl acetate	123-86-4	15-40
Isopropanol	67-63-0	0-17
Cellulose nitrate	9004-70-0	0-20
Ethyl Alcohol	64-17-5	0-15
Triphenyl Phosphate	115-86-6	0-10
n-Propyl acetate	109-60-4	0-10
n-Butyl Alcohol	71-36-3	0-7
Diacetone alcohol	123-42-2	0-6
Camphor	76-22-2	0-3

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST-AID MEASURES

First Aid Measures

General Advice	Provide this SDS to medical personnel for treatment.
Eye Contact	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center or doctor/physician.
Skin Contact	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation or rash occurs: Get medical advice/attention.
Inhalation	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/physician.
Ingestion	IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell.

Most important symptoms and effects

Symptoms	Harmful if inhaled. Causes serious eye damage. May cause drowsiness or dizziness. May be harmful if swallowed. Causes mild skin irritation.
-----------------	---

Indication of any immediate medical attention and special treatment needed

Notes to Physician	Treat symptomatically.
---------------------------	------------------------

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Small Fire	Carbon dioxide (CO2). Foam. Dry chemical.
Large Fire	Use foam or water spray.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical

Flammable liquid and vapor. Keep containers cool with water spray to prevent container rupture due to steam buildup.

Hazardous Combustion Products Nitrous oxide. CO and CO2. Smoke.

Sensitivity to Static Discharge Take precautionary measures against static discharge.

Protective equipment and precautions for firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions	Use personal protective equipment as required. Eliminate all ignition sources. No smoking in spill area.
Environmental Precautions	See Section 12 for additional Ecological Information. Prevent entry into drains, sewers and other waterways.

Methods and material for containment and cleaning up

Methods for Containment	Prevent further leakage or spillage if safe to do so.
Methods for Clean-Up	Absorb spillage with non-combustible, absorbent material. Dispose of contents/container to an approved waste disposal plant. Local authorities should be advised if significant spillages cannot be contained.

7. HANDLING AND STORAGE**Precautions for safe handling**

Advice on Safe Handling	Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges.
--------------------------------	---

Conditions for safe storage, including any incompatibilities

Storage Conditions	Store in a cool, well-ventilated area, away from ignition sources and incompatible materials. Keep container tightly closed. Store locked up.
Incompatible Materials	Strong oxidizing agents. Acids. Alkalis. Peroxides.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Exposure Guidelines**

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethylacetate 141-78-6	TWA: 400 ppm	TWA: 400 ppm TWA: 1400 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 1400 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 1400 mg/m ³
Isopropanol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m ³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m ³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m ³	IDLH: 2000 ppm TWA: 400 ppm TWA: 980 mg/m ³ STEL: 500 ppm STEL: 1225 mg/m ³
n-Butyl acetate 123-86-4	STEL: 200 ppm TWA: 150 ppm	TWA: 150 ppm TWA: 710 mg/m ³ (vacated) TWA: 150 ppm (vacated) TWA: 710 mg/m ³ (vacated) STEL: 200 ppm (vacated) STEL: 950 mg/m ³	IDLH: 1700 ppm TWA: 150 ppm TWA: 710 mg/m ³ STEL: 200 ppm STEL: 950 mg/m ³
Ethyl Alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m ³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m ³	IDLH: 3300 ppm TWA: 1000 ppm TWA: 1900 mg/m ³
n-Propyl acetate 109-60-4	STEL: 250 ppm TWA: 200 ppm	TWA: 200 ppm TWA: 840 mg/m ³ (vacated) TWA: 200 ppm (vacated) TWA: 840 mg/m ³ (vacated) STEL: 250 ppm (vacated) STEL: 1050 mg/m ³	IDLH: 1700 ppm TWA: 200 ppm TWA: 840 mg/m ³ STEL: 250 ppm STEL: 1050 mg/m ³
Triphenyl Phosphate 115-86-6	TWA: 3 mg/m ³	TWA: 3 mg/m ³ (vacated) TWA: 3 mg/m ³	IDLH: 1000 mg/m ³ TWA: 3 mg/m ³

n-Butyl Alcohol 71-36-3	TWA: 20 ppm	TWA: 100 ppm TWA: 300 mg/m ³ (vacated) S* (vacated) Ceiling: 50 ppm (vacated) Ceiling: 150 mg/m ³	IDLH: 1400 ppm Ceiling: 50 ppm Ceiling: 150 mg/m ³
Diacetone alcohol 123-42-2	TWA: 50 ppm	TWA: 50 ppm TWA: 240 mg/m ³ (vacated) TWA: 50 ppm (vacated) TWA: 240 mg/m ³	IDLH: 1800 ppm TWA: 50 ppm TWA: 240 mg/m ³
Camphor 76-22-2	STEL: 3 ppm synthetic TWA: 2 ppm synthetic	TWA: 2 mg/m ³ (vacated) TWA: 2 mg/m ³	IDLH: 200 mg/m ³ TWA: 2 mg/m ³ synthetic

Appropriate engineering controls**Engineering Controls**

Apply technical measures to comply with the occupational exposure limits. Showers. Eyewash stations. Ventilation systems.

Individual protection measures, such as personal protective equipment**Eye/Face Protection**

Wear eye/face protection.

Skin and Body Protection

Wear suitable protective clothing.

Respiratory Protection

In case of insufficient ventilation, wear suitable respiratory equipment.

General Hygiene Considerations Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical State	Liquid	Odor	Not determined
Appearance	According to product specification	Odor Threshold	Not determined
Color	According to product specification		
Property	Values	Remarks • Method	
pH	Not determined	TCC	
Melting Point/Freezing Point	Not determined		
Boiling Point/Boiling Range	75-80 °C / 167-176 °F		
Flash Point	-4 °C / 24 °F		
Evaporation Rate	Not determined		
Flammability (Solid, Gas)	Liquid- Not Applicable		
Upper Flammability Limits	Not determined		
Lower Flammability Limit	Not determined		
Vapor Pressure	Not determined		
Vapor Density	Heavier than air		
Specific Gravity	0.93-1.10		
Water Solubility	insoluble		
Solubility in other solvents	Not determined		
Partition Coefficient	Not determined		
Auto-ignition Temperature	Not determined		
Decomposition Temperature	Not determined		
Kinematic Viscosity	Not determined		
Dynamic Viscosity	Not determined		
Explosive Properties	Not determined		
Oxidizing Properties	Not determined		

10. STABILITY AND REACTIVITY

Reactivity

Not reactive under normal conditions.

Chemical Stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to Avoid

Affected by UV lighting. Store away from direct sunlight.

Incompatible Materials

Strong oxidizing agents. Acids. Alkalis. Peroxides.

Hazardous Decomposition Products

Nitrous oxide. CO and CO₂. Smoke.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure**Product Information**

Eye Contact Causes serious eye damage.

Skin Contact Avoid contact with skin.

Inhalation Harmful if inhaled.

Ingestion Do not ingest.

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Ethylacetate 141-78-6	= 5620 mg/kg (Rat)	> 20 mL/kg (Rabbit) > 18000 mg/kg (Rabbit)	-
Isopropanol 67-63-0	= 4396 mg/kg (Rat)	= 12800 mg/kg (Rat) = 12870 mg/kg (Rabbit)	= 72.6 mg/L (Rat) 4 h
n-Butyl acetate 123-86-4	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 391 ppm (Rat) 4 h
Cellulose nitrate 9004-70-0	> 5 g/kg (Rat)	-	-
Ethyl Alcohol 64-17-5	= 7060 mg/kg (Rat)	-	= 124.7 mg/L (Rat) 4 h
n-Propyl acetate 109-60-4	= 9370 mg/kg (Rat)	> 17760 mg/kg (Rabbit)	-
Triphenyl Phosphate 115-86-6	= 3500 mg/kg (Rat)	> 7900 mg/kg (Rabbit)	-
n-Butyl Alcohol 71-36-3	= 790 mg/kg (Rat)	= 3400 mg/kg (Rabbit)	> 17.7 mg/L (Rat) 4 h = 8000 ppm (Rat) 4 h
Diacetone alcohol 123-42-2	= 4 g/kg (Rat)	= 13500 mg/kg (Rabbit)	-

Information on physical, chemical and toxicological effects

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Carcinogenicity**

The table below indicates whether each agency has listed any ingredient as a carcinogen. However, the product as a whole has not been tested. Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Cellulose nitrate is considered an IARC 2A carcinogen when used in manufacturing of some paints.

Chemical Name	ACGIH	IARC	NTP	OSHA
Isopropanol 67-63-0		Group 3		X
Cellulose nitrate 9004-70-0		Group 2A		X
Ethyl Alcohol 64-17-5	A3	Group 1	Known	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 1 - Carcinogenic to Humans

Group 2A - Probably Carcinogenic to Humans

Group 3 IARC components are "not classifiable as human carcinogens"

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

STOT – single exposure

May cause drowsiness or dizziness

Numerical measures of toxicity

Not determined

12. ECOLOGICAL INFORMATION**Ecotoxicity**

Toxic to aquatic life with long lasting effects.

Component Information

Chemical Name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethylacetate 141-78-6	3300: 48 h Desmodesmus subspicatus mg/L EC50	220 - 250: 96 h Pimephales promelas mg/L LC50 flow-through 484: 96 h Oncorhynchus mykiss mg/L LC50 flow-through 352 - 500: 96 h Oncorhynchus mykiss mg/L LC50 semi-static	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	560: 48 h Daphnia magna mg/L EC50 Static
Isopropanol 67-63-0	1000: 96 h Desmodesmus subspicatus mg/L EC50 1000: 72 h Desmodesmus subspicatus mg/L EC50	9640: 96 h Pimephales promelas mg/L LC50 flow-through 11130: 96 h Pimephales promelas mg/L LC50 static 1400000: 96 h Lepomis macrochirus µg/L LC50		13299: 48 h Daphnia magna mg/L EC50
n-Butyl acetate 123-86-4	674.7: 72 h Desmodesmus subspicatus mg/L EC50	17 - 19: 96 h Pimephales promelas mg/L LC50 flow-through 100: 96 h Lepomis macrochirus mg/L LC50 static 62: 96 h Leuciscus idus mg/L LC50 static	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	72.8: 24 h Daphnia magna mg/L EC50
Ethyl Alcohol 64-17-5		12.0 - 16.0: 96 h Oncorhynchus mykiss mL/L LC50 static 100: 96 h Pimephales promelas mg/L LC50 static 13400 - 15100: 96 h Pimephales promelas mg/L LC50 flow-through	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	9268 - 14221: 48 h Daphnia magna mg/L LC50 10800: 24 h Daphnia magna mg/L EC50 2: 48 h Daphnia magna mg/L EC50 Static

n-Propyl acetate 109-60-4		56 - 64: 96 h Pimephales promelas mg/L LC50 flow-through 56 - 64: 96 h Pimephales promelas mg/L LC50 static		318: 24 h Daphnia magna mg/L EC50
Triphenyl Phosphate 115-86-6	0.6 - 4: 96 h Pseudokirchneriella subcapitata mg/L EC50 static	0.28 - 0.5: 96 h Oncorhynchus mykiss mg/L LC50 static 0.81 - 0.94: 96 h Pimephales promelas mg/L LC50 flow-through 0.53 - 0.8: 96 h Pimephales promelas mg/L LC50 static 0.47 - 1.04: 96 h Lepomis macrochirus mg/L LC50 static 1.2: 96 h Oryzias latipes mg/L LC50 static		0.86 - 1.2: 48 h Daphnia magna mg/L EC50
n-Butyl Alcohol 71-36-3	500: 96 h Desmodesmus subspicatus mg/L EC50 500: 72 h Desmodesmus subspicatus mg/L EC50	1730 - 1910: 96 h Pimephales promelas mg/L LC50 static 1740: 96 h Pimephales promelas mg/L LC50 flow-through 100000 - 500000: 96 h Lepomis macrochirus µg/L LC50 static 1910000: 96 h Pimephales promelas µg/L LC50 static		1983: 48 h Daphnia magna mg/L EC50 1897 - 2072: 48 h Daphnia magna mg/L EC50 Static
Diacetone alcohol 123-42-2		420: 96 h Lepomis macrochirus mg/L LC50 static 420: 96 h Lepomis macrochirus mg/L LC50		8750: 24 h Daphnia magna mg/L EC50

Persistence/Degradability

Not determined.

Bioaccumulation

Not determined.

Mobility

Chemical Name	Partition Coefficient
Ethylacetate 141-78-6	0.6
Isopropanol 67-63-0	0.05
n-Butyl acetate 123-86-4	1.81
Ethyl Alcohol 64-17-5	-0.32
Triphenyl Phosphate 115-86-6	4.59
n-Butyl Alcohol 71-36-3	0.785
Diacetone alcohol 123-42-2	1.03

Other Adverse Effects

Not determined

13. DISPOSAL CONSIDERATIONS

Waste Treatment Methods

Disposal of Wastes

Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging

Disposal should be in accordance with applicable regional, national and local laws and regulations.

US EPA Waste Number

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Ethylacetate 141-78-6		Included in waste stream: F039		U112
n-Butyl Alcohol 71-36-3		Included in waste stream: F039		U031

California Hazardous Waste Status

Chemical Name	California Hazardous Waste Status
Ethylacetate 141-78-6	Toxic Ignitable
Isopropanol 67-63-0	Toxic Ignitable
n-Butyl acetate 123-86-4	Toxic
Cellulose nitrate 9004-70-0	Ignitable Reactive
Ethyl Alcohol 64-17-5	Toxic Ignitable
n-Propyl acetate 109-60-4	Toxic Ignitable
n-Butyl Alcohol 71-36-3	Toxic

14. TRANSPORT INFORMATION

Note

Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT

UN1263, Paint, Hazard Class 3, Packing Group II

IATA

UN1263, Paint, Hazard Class 3, Packing Group II

IMDG

UN1263, Paint, Hazard Class 3, Packing Group II

15. REGULATORY INFORMATION

International Inventories

Chemical Name	TSCA	DSL	NDSL	EINECS	ELINCS	ENCS	IECSC	KECL	PICCS	AICS
Ethylacetate	Present	X		Present		Present	X	Present	X	X
n-Butyl acetate	Present	X		Present		Present	X	Present	X	X
Isopropanol	Present	X		Present		Present	X	Present	X	X
Cellulose nitrate	Present	X				Present	X	Present	X	X
Ethyl Alcohol	Present	X		Present		Present	X	Present	X	X
Triphenyl Phosphate	Present	X		Present		Present	X	Present	X	X
n-Propyl acetate	Present	X		Present		Present	X	Present	X	X
n-Butyl Alcohol	Present	X		Present		Present	X	Present	X	X
Diacetone alcohol	Present	X		Present		Present	X	Present	X	X
Camphor	Present	X		Present		Present	X	Present	X	X

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances

ENCS - Japan Existing and New Chemical Substances

IECSC - China Inventory of Existing Chemical Substances

KECL - Korean Existing and Evaluated Chemical Substances

PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	CERCLA/SARA RQ	Reportable Quantity (RQ)
Ethylacetate 141-78-6	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
n-Butyl acetate 123-86-4	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ
n-Butyl Alcohol 71-36-3	5000 lb		RQ 5000 lb final RQ RQ 2270 kg final RQ

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Isopropanol - 67-63-0	67-63-0	0-17	1.0
n-Butyl Alcohol - 71-36-3	71-36-3	0-7	1.0

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate	5000 lb			X

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Ethyl Alcohol - 64-17-5	Carcinogen Developmental

U.S. State Right-to-Know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsylvania
Ethylacetate 141-78-6	X	X	X
Isopropanol 67-63-0	X	X	X
n-Butyl acetate 123-86-4	X	X	X
Cellulose nitrate 9004-70-0	X	X	X
Ethyl Alcohol 64-17-5	X	X	X
n-Propyl acetate 109-60-4	X	X	X
Triphenyl Phosphate 115-86-6	X	X	X
n-Butyl Alcohol 71-36-3	X	X	X
Diacetone alcohol 123-42-2	X	X	X
Camphor 76-22-2	X	X	X

16. OTHER INFORMATION**NFPA****Health Hazards**

Not determined

Flammability

Not determined

Instability

Not determined

Special Hazards

Not determined

HMIS**Health Hazards**

2

Flammability

3

Physical Hazards

1

Personal Protection

Not determined

Issue Date:

18-Feb-2015

Revision Date:

27-Feb-2015

Revision Note:

New format

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet