CEETSS-3023

V 1.1

Tools Required

13mm Socket

Ratchet

Torque Wrench



Step 2A:

For models w/o factory threaded inserts

1. Insert the (2) M8 bolt plates into factory hexagon holes. Flat plate side in, thread side out.




- 2. Attach the bracket to threaded end of bolt plate and secure with (2) M8 flat washers and (2) M8 hex nuts.
- 3. Secure the bracket to pinch weld with (2) M8 hex bolts, (2) M8 flat washers, (2) M8 hex nuts.



Note:

09-12 models require self-drilling on pinch weld.



Notes

Read this instruction carefully before starting installation.

09-12 models require self-drilling on pinch weld to install brackets.

Proper tools will improve the quality of installation and reduce the time required.

If missing parts or any damage found, please take a picture, and contact us.

Step 1:

- 1. Locate three mounting positions each side.
- 2. Remove the factory tape and clean the sealant and dirt around factory holes on mounting positions.

-1-


3. Clean the factory threaded holes if equipped.

Step 2B:

For models with factory threaded inserts


- 1. Attach the bracket to inner rocker panel and secure with (2) M8 hex bolts, (2) M8 flat washers.
- 2. Secure the bracket to pinch weld with (2) M8 bolt plates, (2) M8 flat washers, (2) M8 hex nuts.

-2-



Step 3:

- 1. Remove (6) M8 hex bolts and (6) M8 flat washers behind the step bar.
- 2. Slide mounting track to proper positions.
- 3. With assistance, lift and attach the step bar to brackets. Secure the step bar on brackets with(6) M8 hex bolts and (6) M8 flat washers.
- 4. Repeat to install the other side step bar, do not fully tighten.





Part List:

	Qty.	Description
1	×6	Mounting Bracket
2	×12	M8 Hexagon Bolt
3	×12	M8 Bolt Plate
4	×24	M8 Flat Washer
(5)	×24	M8 Hexagon Nut
6	×12	M8 Hexagon Bolt (On Step Bar)
7	×12	M8 Flat Washer (On Step Bar)

Step 4:

- 1. Tighten M8 hex bolts and nuts on vehicle with 15 ft. lbs. torque.
- 2. Adjust the step bar to level and tighten M8 hex bolts with 15 ft. lbs. torque.
- 3. After the step bar installed, periodic check to ensure all mounting hardware remains secure and tight.





Driver Left Side Front







1









7