

**Product Code:** 11002

**Description:** Standard Analogue 1 Module 24 hr Timer



### General Information

Dimensions (mm)	90 x 17.5 x 64.5
Display	Mechanical Dial
Time Base	Quartz Crystal
Quartz Crystal Accuracy (at 20°C)	≤ ± 0.5 Seconds / Day
Materials	Self-Extinguishing Thermoplastic
Mounting	Surface Mounting or DIN
Distribution Board Mounting	35mm DIN-rail (DIN EN 60715)
Module Size	1
Warranty (Years)	3

### Programming

Programming Schedule	24 Hour
Available Operations	96 Operations
Switching Modes	ON, OFF, Permanent On/Off
Minimum Interval (Mins)	15
Program Security	Unlimited (E2-PROM)

### Supply & Power

Supply Voltage (V AC)	230
Power Consumption (W)	0.4
Cable Size (mm <sup>2</sup> )	0.5 - 2.5
Power Reserve @ 20°C	100 Hours (Approx.)

### Environment

Ingress Protection	IP20
Operating Temperature (°C)	-5 to +50

**Supplied** . .

### Features

Simple Programming with 15 min Captive Segments  
 Simple to Read Switching  
 Manual Override Switch "Permanent OFF/Automatic/Permanent ON"  
 100 Hour Battery Reserve

### Outputs

Number of Outputs	1
Total Switch Rating (Inductive)	230V AC, 16A @ 1.0pf 2.5A @ 0.6pf
Contact Type	SPST
Maximum LED Lamp Load Rating (W)	200 @ 230V
Contact Material	AgSnO <sup>2</sup>
Maximum Incandescent, Halogen Lamp Load Rating (W)	2000
Maximum Compact Fluorescent Lamp Load Rating (W)	200
Maximum Incandescent Lamp Load Rating (W)	2000
Maximum Fluorescent Lamp (Uncompensated) Load Rating (W)	1000
Maximum Fluorescent Lamp (Series Compensated) Load Rating (W)	750
Maximum Fluorescent Lamp (Parallel Compensated) Load Rating (W)	550
Minimum Switching power (mW)	1000 (10V/10mA)

### Accessories

143602: Module Enclosure