

CALDER LEAD'S THE WAY

APPLICATION BY CODE

Rolled Lead Sheet to BS EN 12588 - thickness to tolerances of $\pm 5\%$

CODE	THICKNESS (MM)	KG PER M ²	SOAKERS	FLASHINGS	FLAT ROOFING	PARAPET & TAPERED VALLEY GUTTERS	PITCHED ROOFS	VERTICAL CLADDING	DORMERS	BAY ROOFS & CANOPIES
3	1.32	14.97								
4	1.80	20.41								
5	2.24	25.40								
6	2.65	30.05								
7	3.15	35.72								
8	3.55	40.26								
ANCILLARY PRODUCTS PER APPLICATION			1	1, 2, 3, 4	1, 4, 5, 6, 7, 8	1, 4, 5, 7, 8, 9	1, 4, 5, 6, 7, 8	1, 4, 5, 6, 7, 8, 10	1, 4, 5, 6, 7, 8	1, 4, 5, 6, 7, 8

1. PATINATION OIL 2. LEAD SHEET SEALANT 3. CALDER FIXING CLIP 4. CALDER RETAINING STRIPS 5. NAILS
6. WOOD CORE ROLL 7. GEOTEC UNDERLAY 8. BUILDING PAPER 9. EXPANSION JOINT 10. DOME HEAD SCREWS

For correct fixing details refer to our Technical Team. Email on technical@calderlead.co.uk



With over 260 years' experience, Calder is one of the oldest and largest manufacturers of Rolled Lead Sheet which is made using 100% recycled materials and to BS EN 12588.

www.calderlead.co.uk



CALDER LEAD'S THE WAY

NOMINAL ROLL WEIGHTS

Rolled Lead Sheet to BS EN 12588 - thickness to tolerances of $\pm 5\%$

WIDTH (MM)	CODE 3		CODE 4		CODE 5		CODE 6		CODE 7		CODE 8	
	3M / KG	6M / KG	3M / KG	6M / KG	3M / KG	6M / KG	3M / KG	6M / KG	3M / KG	6M / KG	3M / KG	6M / KG
150	7	13	9	18	11	23	14	27	16	32	18	36
180	8	16	11	22	14	27	16	32	19	39	22	43
240	11	22	15	29	18	37	22	43	26	51	29	58
300	13	27	18	37	23	46	27	54	32	64	36	72
360	16	32	22	44	27	55	32	65	39	77	43	87
390	18	35	24	48	30	59	35	70	42	84	47	94
450	20	40	28	55	34	69	41	81	48	96	54	109
600	27	54	37	73	46	91	54	108	64	129	72	145
760	34	68	47	93	58	116	69	137	81	163	92	184
800	36	72	49	98	61	122	72	144	86	171	97	193
900	40	81	55	110	69	137	81	162	96	193	109	217
1000	45	90	61	122	76	152	90	180	107	214	121	242
1200	54	108	73	147	91	183	108	216	129	257	145	290
2400	108	216	147	294	183	366	216	433	257	514	290	580
THICKNESS (MM)	1.32		1.80		2.24		2.65		3.15		3.55	
WEIGHT PER M ²	14.97		20.41		25.40		30.05		35.72		40.26	

To calculate the approximate weight of a piece of Rolled Lead Sheet multiply the length in metres by the width in metres and then multiply by the Code weight per m² shown in the above table.

Whether you have a general enquiry, a challenging roofing design, need an in depth surveying and report service, specification support or a take-off service, our dedicated Technical Advisory team will provide you with an expert, professional and reliable service.

Email: technical@calderlead.co.uk | Tel: 01244 393710



Jupiter Drive,
Chester, CH1 4EX.



0191 482 7350



sales@calderlead.co.uk



www.calderlead.co.uk

