Capital Multi Stock







Ibstock Code:0717Type:StockFacing Description:SandfacedDry Brick Weight (kg):2.3kgPack Quantity:475Packaging (standard):Banded (plastic)Factory:Banded (plastic)Technical Specification (to BS EN 771-1)215x102x65Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:215x102x65Configuration:Single FrogVoids (%):Single FrogCompressive Strength (N/mm²):25Active Soluble Salts:S2Vater Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Sio335008973	Product Information	
result Sandfaced Facing Description: Sandfaced Dry Brick Weight (kg): 2.3kg Pack Quantity: 475 Packaging (standard): Banded (plastic) Factory: Laybrook Factory: Laybrook Technical Specification (to BS EN 771-1) Laybrook Size Tolerances Mean & Range: 215x102x65 Size Tolerances Mean & Range: 72 R1 Configuration: Single Frog Voids (%): 8-13 Compressive Strength (N/mm²): S2 Active Soluble Salts: S2 Vater Absorption (% weight): 14 Durability: F2 Gross Dry Density (Sound Insulation) (Kg/m³): 1520 Equivalent Thermal Conductivity "K" value 5% Exposed: Refer to Ibstock	Ibstock Code:	0717
Dry Brick Weight (kg):2.3kgPack Quantity:475Packaging (standard):Banded (plastic)Factory:LaybrookFactory:12st102x65Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):8-13Compressive Strength (N/mm²):25Active Soluble Salts:S2Vater Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m²):520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockIntial Rate of Absorption (Suction Rate) (Kg/m²/min):Sert on Ibstock	Туре:	Stock
Pack Quantity:475Packaging (standard):Banded (plastic)Factory:LaybrookFactory:LaybrookFactor (to BS EN 771-1)215x102x65Size Tolerances Mean & Range:72 R1Configuration:Single FrogVoids (%):8-13Compressive Strength (N/mm²):25Active Soluble Salts:S2Vater Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m²):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockIntial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Facing Description:	Sandfaced
Packaging (standard):Banded (plastic)Factory:LaybrookFacthical Specification (to BS EN 771-1)15x102x65Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):8-13Compressive Strength (N/mm²):25Active Soluble Salts:S2Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInital Rate of Absorption (Suction Rate) (Kg/m²)min):Refer to Ibstock	Dry Brick Weight (kg):	2.3kg
Factory:LaybrookTechnical Specification (to BS EN 771-1)LaybrookBrick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):8-13Compressive Strength (N/mm²):25Active Soluble Salts:S2Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Pack Quantity:	475
Technical Specification (to BS EN 771-1)Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):8-13Compressive Strength (N/mm²):25Active Soluble Salts:S2Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Packaging (standard):	Banded (plastic)
Brick Dimensions (L x W x H mm):215x102x65Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):8-13Compressive Strength (N/mm²):25Active Soluble Salts:S2Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Factory:	Laybrook
Size Tolerances Mean & Range:T2 R1Configuration:Single FrogVoids (%):8-13Compressive Strength (N/mm²):25Active Soluble Salts:S2Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Technical Specification (to BS EN 771-1)	
Configuration:Single FrogVoids (%):8-13Compressive Strength (N/mm²):25Active Soluble Salts:S2Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Brick Dimensions (L x W x H mm):	215x102x65
Voids (%):8-13Compressive Strength (N/mm²):25Active Soluble Salts:S2Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Size Tolerances Mean & Range:	T2 R1
Compressive Strength (N/mm²):25Active Soluble Salts:S2Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Configuration:	Single Frog
Active Soluble Salts:S2Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Voids (%):	8-13
Water Absorption (% weight):14Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Compressive Strength (N/mm ²):	25
Durability:F2Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Active Soluble Salts:	S2
Gross Dry Density (Sound Insulation) (Kg/m³):1520Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Water Absorption (% weight):	14
Equivalent Thermal Conductivity "K" value 5% Exposed:Refer to IbstockInitial Rate of Absorption (Suction Rate) (Kg/m²/min):Refer to Ibstock	Durability:	F2
Initial Rate of Absorption (Suction Rate) (Kg/m ² /min): Refer to Ibstock	Gross Dry Density (Sound Insulation) (Kg/m ³):	1520
	Equivalent Thermal Conductivity "K" value 5% Exposed:	Refer to Ibstock
EAN: 5036335008973	Initial Rate of Absorption (Suction Rate) (Kg/m²/min):	Refer to Ibstock
	EAN:	5036335008973

09/04/2021