

FONODAN 50

Auto-adhesive tape for acoustic insulation of plasterboard walls: Stud and track framing.



EPD[®]



EPD S-P-04340

FONODAN 50 is a two layer product made of a self-adhesive high density bitumen membrane thermally bonded to a cross-linked polyethylene. FONODAN 50 acoustically works as spring between the gypsum board and frame.

Presentation

- Length (cm): 1000
- Width (cm): 4.6
- Thickness (mm): 3.9
- Thickness (mm) ~ Standard: EN 1923
- m² / package: 3.22
- ml/pallet: 42.3
- Surface (m²): 0.46
- Product code: 610202

Technical Data

Concept	Value	Standard
Mass per unit area (nominal) (kg/m ²)	3	-
Mejora del nivel de ruido aéreo entre placas, ΔRA	>3	EN 140-1
Thermal conductivity of cross-linked polyethylene (W / m K)	<0.040	EN 12667
Remainder deformation (24h compressed at 50%, 23°C) (%)	<35	EN 1856
Reaction to fire	F	EN 13501-1
Dynamic stiffness (MN/m ³)	<= 100	EN 29052-1

Concept	Value	Standard
Hazardous substances	PND	-
Work temperature (°C)	>10	-
Thickness tolerance (%)	+/- 0,2	EN 823
Tolerance Length and Width (%)	1	EN 822
Hysteresis work (Nm)	>1.9	EN 3386-1

Environmental Information

Concept	Value	Standard
Volatile organic compounds (COV's) ($\mu\text{g}/\text{m}^3$)	15	ISO 16000-6:2006
Content of recycled raw material (%)	14,4	-
Pre-Consumer recycled content (%)	100	-
Manufactured in	Fontanar (Guadalajara) España	-

Standards and Certification

- The sound certifications are the result of tests in an approved laboratory.
- *For any questions about information on the tests, please consult our Technical Department.

Laboratory	Test (EN 140-3) No	Result (EN 717-1)
E.U.I.T.T (1)	UPLA 053/01	RA= 37 dBA
E.U.I.T.T (2)	UPLA 054/01	RA= 42.3 dBA

(1) N13 + 50 air cavity + N13

(2) N13 + mineral wood 40 + N13

Scope

- Impact sound insulation of floorboards.
- Self-adhesive anti-resonant strip for the improvement of the plasterboard structure.
- Anti-resonant strip for metal structures on tiled roofs.

Advantages & Benefits

- Acoustic insulation $D_nTA > 50$ dBA.
- By shifting the frequency of coincidence, the lack of privacy that occurs due to the loss of insulation at the previous frequencies (where the human ear is most sensitive) decreases.
- Easy and quick to install.

- High resistance to tearing.
- Improvement of airborne sound level between rigid elements $\Delta RA > 3$ dBA.
- Improves the sound insulation of partition walls or wall linings in single-panel systems by minimising the hollow sound.

Instruction for Use

Preliminary operations

- The channel is riveted to the floating floor and the roof. See Danosa Solutions Manual DIV2 and FCH3.
- The gutter is riveted to the floating floor and the roof. See tab AA 11 and AA 12 of the Danosa Sound Insulation Solutions Manual.
- The uprights are then placed every 60 or 40 cm depending on the height and the plasterboard system.
- Once the structure is in place, the FONODAN 50 is adhered following the steps below:

Laying FONODAN 50

- The non-stick plastic is removed from the beginning of the roll and the product is glued to the side of the channel.
- Once the beginning of the roll is attached, the plastic is removed and the band is pressed to the side of the carcass.
- The same procedure is followed for the uprights.
- It is not necessary for the FONODAN 50 strip to be completely end-to-end, as there may be small discontinuities. The important thing is that it is fixed in such a way that it cushions the rigidity of the panel.
- Once the entire structure is covered on the plate side, it is fixed with sheet metal screws according to the proposed system.
- The gypsum plasterboards are sealed and taped according to the criteria of the respective manufacturer.

Laying on tile battens.

- Once the battens have been laid, the Fonodan 50 is fixed according to the previous section.

Laying on wooden battens.

- Once the levelling mortar has been cleaned and the timber framework has been prepared, it is fixed to the base of the framework as described in "Laying Fonodan 50".
- For greater effectiveness of the system, it is recommended to fix the framework with staples on top of it, making a floating frame.
- Finally, fix the decking to the framework with nails 2 cm longer than the thickness of the wood strip.

Indications and Important Recommendations

- The floating mortar must be strong enough to prevent cracking. (See SPD No. 1.3).
- The facade cladding in a building must end at the dividing wall between different users. See SPD 2.1
- Installations or elements liable to cause vibrations inside the partition walls shall be protected by cross-linked PE shells. See SPD 2.3
- The structure's anchorages must not be fixed to the building structure except on the roof. See SPD 3.2
- In order for the system to be perfectly determined by the insulation, no unwanted lateral transmissions must occur.

- Set back the partition wall on the pillars.
- Impact sound insulation (e.g. Impactodan System) must be used. See SUF1, SUF2 and SUF3 data sheets.
- It will be taken into account that this product is part of a Sound Insulation system, so the Danosa Constructive Solutions Catalogue, Sound Insulation Commissioning must be taken into account. "Details of Singular Points" (SPD), as well as the rest of the Danosa documentation.
- Isolated sewage disposal systems with FONODAN BJ or ACUSTIDAN. See BAJ1 and BAJ2 sheet of "Danosa Sound Insulation Solutions."

Handling, storage and preservation

- Store in covered and ventilated places that comply with current legislation regarding storage.
- Consult the product safety datasheet.
- The product, as such, is not classified as hazardous for transportation.
- Under normal conditions, the product is not hazardous.
- In application, the appropriate measures must be taken when handling tools.
- Stable at room temperature. Avoid being at temperatures above 70°C as that would alter the material's properties, accelerating its degradation.
- This product should not be installed when the ambient, product or support temperature is below +10°C.
- For further information, please contact our Technical Department.
- No personal protection is required during transportation and handling.
- In all cases, the Occupational Safety and Hygiene standards, as well as the standards of good construction practice, must be taken into account.

Notice

- The information contained in this document and any other advice provided, are given in good faith, based on DANOSA's current knowledge and experience when products are properly stored, handled and applied, in normal situations and in accordance with the recommendations of DANOSA. The information applies only to the application (s) and the product (s) to which reference is expressly made. In case of changes in the parameters of the application, or in case of a different application, consult the DANOSA Technical Service before using the DANOSA products. The information contained herein does not exonerate the responsibility of the building agents to test the products for the application and intended use, as well as their correct application in accordance with current legal regulations. The product images used in our communications are indicative and may differ slightly in color and aesthetic appearance in relation to the final product. Orders are accepted in accordance with the terms of our current General Sales Conditions. DANOSA reserves the right to modify, without prior notice, the data reflected in this documentation. Website: **danosa.com/en-gb** E-mail: **info@danosa.com** Telephone: **+44 845 074 0553**