

armorgard



Data Sheet | Model:

Armorgard FlamBank FBC5



- Keyed alike 5-lever deadlocks.
- Unique external and internal anti-jemmy system.
- Robust construction using 2mm and 3mm steel.
- Hydraulic gas arms to assist with the lid opening.
- Autolatch lid stay to secure the lid in the open position.
- High and low level ventilation to prevent build-up of fumes.
- Flame arrester gauze fitted.
- The FlamBank is built to the specification of 30 minute fire resistance
- Suitable for storing flammable equipment or chemicals.
- Fully welded sump to comply with COSHH regulations and prevent any leakages.
- Fork lift skids with fixing holes to add castors and make it a mobile unit.
- Facilities to fix the unit in position.
- Comes complete with 1 shelf.
- Complete with relevant signage.

Product	Armorgard FlamBank FBC5
Internal dimensions	1500x605x1185mm
External dimensions (including protrusions)	1585x675x1275mm
Weight (kg)	174
Colour	Pillar Box Red: RAL 3020
Finished Coating	Powder coated steel
Material	Steel
Material Thickness	2mm and 3mm
Locking mechanism	2x highly secure, keyed alike 5-lever deadlocks
Does it have Forklift Skids?	Yes
Does it have Gas Arms?	Yes
Newton Loading of Gas Arms	1000N
Safety stay	Yes
Quantity of keys supplied	3 keys
Optional Extras Available	Castors, shelves
Quantity of Shelves as standard	1
Are Castors standard or optional extra	Optional Extra
How are the Castors fitted?	Quick-fix bolt on castor kit
Sump capacity	110L
Safety Signage	Hazardous goods sign
Fire resistant?	Yes

Armorgard Ltd, Unit 14-16, Standard Way, Fareham Industrial Park, Fareham, Hampshire, PO16 8XB Call 023 9238 0280 Email sales@armorgard.co.uk www.armorgard.co.uk VAT Reg No: 189 2967 40 Registered in England & Wales No. 08452262. Registered Office at the above address.

