

AUTOADHESIVE TAPE FOR THE ACOUSTIC INSULATION OF DOWNSPOUTS





Airbourne acoustic insulation



Greater sound protection



Autoadhesive



Minimal thickness, easy application



Greater tear resistance

FONODAN® BJ is a two-layer tape formed by a self-adhesive membrane of high density and a chemically cross-linked polyethylene therm-welded to the previous one. Eliminates the resonance frequencies in metal and PVC downpipes.

ADVANTAGES

- Insertion loss IL > 17dBA (complete system).
- Self-adhesive product which is easy and quick to install.
- Minimal thickness, easily adapts to the downspout.
- High resistance to tearing, does not break when installed.
- The double reinforcement at elbows and joints further increases the acoustic performance.
- Prevents the onset and appearance of mold in the insulation.

USES

- Specially designed to minimise the noise of evacuation pipes in all types of buildings.
- FONODAN® 130 increases the insulation in the noisest area area of the downpipe, such as junctions and bends.
- FONODAN® 70 reduces the noise of pipes and suspended pipes in false/suspended ceilings.

ENVIRONMENTAL INFORMATION

Volatile organic compounds (COV's) = $15 \mu g/m^3$ according to ISO 16000-6:2006










METHOD OF APPLICATION

• Apply in temperatures over 10°C.







- 1.- Cut the roll to the lenght of the drain taking care not to damage the strip.
- 2.- Remove the non-stick plastic film.



5.- Secure the flanged pipes and the siphon tube with FONODAN® 70 with cable ties.





- **3.-** Adjust the piece with the self-adhesive face towards the downspout, fasten with flanges.
- 4.- Reinforce the elbow with the FONODAN® 130.

PRODUCT RANGE

Product name	Thickness	Dimensions	Rolls/
	(mm)	(m)	pallet
FONODAN® BJ	4	0,47 x 10	32

ANCILLARY PRODUCT RANGE

Product name	Thickness (mm)	Dimensions (m)	Rollos/ box
FONODAN® 70	4	0,066 x 10	8
FONODAN® 130	4	0,132 x 10	4

COMPATIBLE SOLUTIONS



