

## SELF-ADHESIVE TAPES WITH METAL SELF-PROTECTION FOR SEALING CHIMNEYS, TUBES, ROOFLIGHTS, CRACKS, ETC



Watertight



High flexibility



Weather resistant



Resistant to UV



Flame-free  
Easy installation



Good application  
to support

SELDAN® tapes are self-adhesive waterproofing tapes composed of a bituminous bituminous mastic (SBS), with an aluminum sheet as a protective material on its outer face and a non-stick plastic film on its inner face.

### ADVANTAGES

- Completely waterproof.
- High flexibility.
- Weather resistant to both high and low temperatures. Perfect for typical UK weather.
- Resistant to UV rays.
- Easy and quick to install, self-adhesive material.
- Great application to angular and irregular surfaces.

### USES

- SELDAN® self-adhesive tapes are used for many types of sealing:
- Sealing of covers and pavements.
  - Sealing of thermal insulation panels.
  - Sealing of joints and overlaps.
  - Sealing of gutters, valleys, eaves, and other roof details.
  - Sealing of chimneys, pipes, breastplates, mortar cracks, downspouts, etc.
  - Waterproofing of pitched roofing meeting with verticals.
  - Sealing of metal and fiber cement panels, tiles, metal covers, etc.
  - Sealed skylights.



## METHOD OF APPLICATION

- Cleaning the support.
- Apply bituminous primer on mortar and concrete substrates.
- On low porous or metallic substrates, perform an adhesion test.
- A bituminous primer must be applied to walls.
- Cut the piece of tape necessary to cover the surface to be treated.
- Remove the nonstick coating and press the surface.

## PRODUCT RANGE

Product name	Colour	Tape width	Roll length	Rolls/Box
<b>SELF-DAN®</b> Metal self-protection (aluminium 60 microns)	Natural	10 cm	10 m	12
	Red	15 cm		8
	Grey			
	Natural	30 cm		4
	Red			
	Grey			

## APPLICATION TEMPERATURE

- From 10 °C.
- Do not apply on icy or wet surfaces.

## PRECAUTIONS & STORAGE

- Check the possible incompatibility between thermal insulation and waterproofing.
- Check for possible incompatibility with existing waterproofing.
- Do not use to protect polyurethane foam without previously placing a suitable separating layer.
- Store in a dry place, protected from rain, sun and high and low temperatures.
- The product should be stored in vertical position.
- The pallets will not stack. If you want to store in height, the shelves should have crossbars or reinforcements under the wooden pallet.
- Before pallet handling, the retractable state will be checked to reinforce it if necessary.

## COMPATIBLE USES

