



Product Specification

Ludus

Applications	Gardens, terraces, commercial properties and exhibitions
Fibres	UV-Stabilized XST (Xtra Spine Technology) 3 colours Curled
Production method	Tufting
Gauge	3/8"
# tufts/m²	ca. 24.150/m²
Pile height	ca. 30 mm
Pile weight	ca. 1113 gr/m²
Total weight	ca. 2083 gr/m²
Tuft cloth	Polypropylene, UV-Stabilized, ca. 170 gr/m²
Backing	ca. 800 gr/m²
Infill	No infill
Roll width	4m
Colour	Medium green
Colour fastness	Scale 7 (DIN 54004)
UV-stability	> 3.000 hours UV-A
Chlorine resistance	4-5 (DIN 54019)
Resistance to sea water	4-5 (DIN 54007)

This product specification is for information purposes only. When publishing product information on your owned digital media such as your website or social media, please publish a reduced version of this information. We kindly ask that you do not upload to digital media or share with third parties.

Namgrass reserves the right to amend technical specifications on the product. Delivered products can slightly differ from this technical data. Namgrass guarentees the technical quality of the product.

Namgrass UK, Redcliffe, Bashley Road, New Milton, Hampshire BH25 5RY T 01425 627832F 01425 614495

namgrass.co.uk info@namgrass.co.uk