

Product Specification

Serenity

Fibres	65 % Polyethylene / 35 % Polypropylene straight / curled
Fibre Shape	Xtra Spine Technology (XST)
Production Method	Tufting
Guage	3/8"
Stitches	ca. 260st / lm
# tufts/m²	ca. 27,300 / m²
Pile Height	ca. 38mm
Pile weight (g/m²)	ca. 1555 gr / m²
Total weight (g/m²)	ca. 2555 gr / m²
Tuft cloth (g/m²)	Polypropylene woven, ca. 170 gr / m²
Backing (g/m²)	Latex Pre coat ca. 800 gr / m²
Roll length	30m
Colour Fastness	Scale 7 (DIN 54004)
UV Stability	> 3,000 hours UV-A 6,000 hours XENON

This product specification is for information purposes only. When publishing product information on your owned digital media such as your website or social media, please publish a reduced version of this information. We kindly ask that you do not upload to digital media or share with third parties.

Namgrass reserves the right to amend technical specifications on the product. Delivered products can slightly differ from this technical data. Namgrass guarantees the technical quality of the product.

Namgrass UK, Redcliffe, Bashley Road, New Milton, Hampshire BH25 5RY T 01425 627832F 01425 614495

namgrass.co.uk info@namgrass.co.uk