

Product name	Product	group	Production location	
Alexia	D5		Hedikhuizen	
Colour				
red-brown with light and dark shades				
Format				
Moulding met	od Hand form			
DF: 214 x 101 x 65 mm Between bat		he average size and color may slightly differ.		
Essential Characteristics - EN771-1				
	CE	0620-CPR-978	380	
Dimensional tolerances	T2			
Range	R1			
Active Soluble Salts	S2			
Mean Compressive strength	>= 20 N/mm²	Tested to the	bed face	
Normalized Compressive strength	>= 20 N/mm²	Tested to the bed face		
Dimensional stability	NPD			
Bond Strength general	0,15 N/mm²			
Bond Strength thin layer	0,30 N/mm²			
Reaction to fire	A1	Category		
Water absorption	<= 10% m/md			
Water vapour permeability	50/100			
Net dry density	2050 kg/m³ (D1)			
Gross dry density	1880 kg/m³ (D1)			
Thermal conductivity Lambda 50/50	<=0,60 W/m.K			
Durability against freeze thaw	F2			
Dangerous substances	NL-BSB	According to	Annex ZA 3	
Other Characteristics				
Initial rate of water absorption - Non-coated Bricks	1,5 - 4,0 kg/m².min (IW3)	Value accordi	ng EN771-1:2011 - 5.3.8	
Initial rate of water absorption - Coated bricks	0,5 - 1,5 kg/m².min (IW2)	Value accordi	ng EN771-1:2011 - 5.3.8	
Freeze/thaw resistance	NPD	B 27-009		
Thermal conductivity Lambda 90/90	NPD			
Thermal conductivity Lambda Ui	NPD			
Thermal conductivity Lambda Ue	NPD			









Cutting



Storage & handling	

- Store packs on a clean surface and cover them
 Process from multiple packs at the same time
 Follow the Vandersanden processing guidelines

Cutting with power tools may generate dust. This dust may contain silica or quartz particulate which may constitute a hazard. Persons undertaking work of this nature are advised to wear dust masks (FFP3).

*All our Coated bricks are only coated on the facing sides. Coated products are specially labeled and recognisable with a "C" logo on the top left-hand side of the packaging. Always check if using coated or non-coated bricks. Match the mortar to the specified initial water absorption.