



Branches

Sandbach	t. + 44 (0) 1270 902020
Basingstoke	t. + 44 (0) 118 9819522
Ireland	t. + 353 (0) 719638796

Data Sheet

Wood Fibre Fillerboard

Bitumen Impregnated

Multi purpose bituminous Wood Fibre Fillerboard for is used as an expansion joint filler for concrete slab and wall construction.



Performance and Composition

Width	Sheet = 1220mm Strips = 100, 150 & 200mm
Length	2440mm
Thickness	12, 20 & 25mm
Thickness Tolerance	+/- 1.2mm
Density	220 - 300 kg/cbm
Humidity	4 - 6.5%
Heat Condition Coefficient	0.052 W/mk
Swelling after 2hrs in Water	Approx 6%
Hygienic Class	E 1
Sound Absorptions	Approx 40 dB
Transverse Internal Bend	1.2 N/mm2
Flammability Class	B 2
European Norms	EN 13986 & EN622-4
American Norms	ASTM D 1751 acc. to compression, extrusion, recovery Test procedure acc. to ASTM D 545 99
Contents of Bitumen	More than 10%
Certification of Production	FSC, ISO 9001:2000
Ingredients	Wood fibre, Bitumen, Water Repellent, Paraffin

Packaging Strips

Size (mm)	Pack quantity	Packs per Pallet
12 x 100	20	54
12 x 150	10	72
12 x 200	10	54
20 x 100	12	60
20 x 150	6	80
20 x 200	6	60
25 x 100	10	54
25 x 150	5	72
25 x 200	5	54

Packaging Sheets

Size (mm)	Pallet quantity
12	95
20	63
25	45

Head Office

Units 1-3 Shannon Industrial Estate, Lodge Road, Sandbach, Cheshire, CW11 3HP
 e. info@euroacc.co.uk ■ w. www.@euroacc.co.uk