

Product Code: PSPBF

Description: Powersaver Plus Electronic Fused Boost Controller with Single Button Operation



General Information

Dimensions (mm)	86 x 86 x 35
Depth Without Back Box (mm)	12
Flush Mounting Back Box Depth (mm)	25
Finish	White Gloss
Materials	ABS
Mounting	Single Pattress – Surface and Flush Mounting
Warranty (Years)	3

Programming

Selectable Boost Durations | 30 Minutes, 1 Hour or 2 Hours

Supply & Power

Supply Voltage (V AC)	230
Frequency (Hz)	50
Fuse Fitted (BS1362)	13A
Maximum Cable Size (mm ²)	2.5 (Flex), 4.0 (Fixed)
IEC Protection Class	Class II

Environment

Ingress Protection	IP20
Operating Temperature (°C)	-10 to +40
Temperature Rating	T40

Supplied BS1362 13A Fuse

Outputs

Number of Outputs	1
Switched Output	240V AC, DPST
Maximum LED Lamp Load Rating (W)	200 @ 230V
Maximum Incandescent, Halogen Lamp Load Rating (W)	1000
Maximum Fluorescent Lamp Load Rating (W)	500
Maximum Compact Fluorescent Lamp Load Rating (W)	100
Maximum Fluorescent Lamp Load Rating (W)	500

Accessories

PSPFUSE - Powersaver Plus Spare Fuses

