

## BZ12 - Bizweld Cape Hood

**Collection:** Bizweld™

**Range:** Flame Resistant

**Inner Pack:** 10

**Outer Carton:** 50

### Product information

Designed to give maximum protection and comfort to the wearer, the Bizweld cape hood will help keep you safe in dangerous work environments. The cape hood is made with a self fabric drawcord to allow for adjustment for a comfortable fit. Must be worn with a suitable coverall or jacket/trouser combination.

### Bizweld™

The garments in the Bizweld Flame Resistant range have been specially designed to guarantee comfort, performance and safety whilst providing effective function at all times. This range has been rigorously tested to ensure total compliance with the latest international standards.

### Flame Resistant

This industry leading flame resistant range provides multi standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

### Standards

EN ISO 11612 (A1+A2, B1, C1, E2, F1)

EN ISO 11611 Class 1 (A1+A2)

ASTM F1959/F1959M-12 (ATPV 11.2 CAL/CM<sup>2</sup> (HAF = 80.4%))



### Features

- Protection against radiant, convective and contact heat
- Certified protection against molten metal splash
- Designed with a comfort fit
- CE-CAT III
- 40+ UPF rated fabric to block 98% of UV rays
- CE certified

| Range |                     |
|-------|---------------------|
| Navy  | one_size - one_size |

### BZ12 - Bizweld Cape Hood Commodity Code: 6217100090

#### Test House

Cert No: 2777\_12872\_01\_E00\_00

#### Wash Care



#### CARTON DIMENSIONS/WEIGHT

| Item    | Colour | Len  | Wid  | Hgt  | Weight (Kg) | Cubic (m <sup>3</sup> ) | EAN13         | DUN14          |
|---------|--------|------|------|------|-------------|-------------------------|---------------|----------------|
| BZ12NAR | Navy   | 43.0 | 28.0 | 35.0 | 0.2400      | 0.0421                  | 5036108193912 | 15036108680211 |