



SKIMCOAT

Thin Coat Plaster

Product Data and Submittal Sheet

Description

- **SKIMCOAT** is a gypsum-based thin plaster which can be applied on wide range of surfaces.
- **SKIMCOAT** is a multipurpose plaster for gypsum and cement based undercoat plasters, masonry and plasterboard surfaces.
- Its long workability time enables an easy application with a low waste rate.
- **SKIMCOAT** can be applied easily. Corrects cracks and defects on the surfaces.
- It is easy to prepare **SKIMCOAT** mortar compare to conventional plasters.
- **SKIMCOAT** creates a smooth surface.
- Easy to use for repairs and maintenance.
- **SKIMCOAT** provides white surfaces.

Method of Application

- Dust and substances preventing adherence on the surface must be removed before the application.
- 25 kg of **SKIMCOAT** should be mixed with approximately 11,5 lt of clean water.
- Add some water in a clean bucket. Add **SKIMCOAT** until it covers the water surface. Wait for a few minutes, then mix the mortar with a mechanical whisk until it gains a right consistency for application.
- Mortar in the bucket should be used within approximately 60 minutes.
- **SKIMCOAT** is applied to the whole surface with a trowel and to finish the application, second coat of **SKIMCOAT** is applied. Total thickness of **SKIMCOAT** may vary according to substrate.
- For 1 mm of application per 1m² approximately 1,1 kg of **SKIMCOAT** is consumed.

Recommendations

- Use a low-speed mechanical whisk.
- Dry and hot surfaces should be dampened before the application.
- Do not add any water or plaster to the mortar after mixing completed.

Storage Conditions

- Maximum 2 pallets of **SKIMCOAT** bags should be stacked one on top of another.
- Bags are recommended to be consumed within 9 months provided that they are stored on pallet in a dry and indoor environment.
- Poor storage conditions or exceeding shelf life may reduce **SKIMCOAT**'s performance.

RIGHTFINISH

