

## USB-C to 2.5G Ethernet Adapter

Part number: K38285WW | UPC code: 085896382850

Increase productivity and decrease down time.

Increase productivity and decrease down time. The USB-C to 2.5G Ethernet Adapter delivers transfer speeds up to 2.5 times faster than current solutions, providing a reliable connection and rapid data transfer speeds.\* Bus-powered, with no power supply needed — simply connect it, and it works. Two-year warranty.

#### Features include:

- up to 2.5 times faster than current 1Gbps speeds
- · increased productivity, decreased down time
- · bus-powered
- · 2-year warranty





<sup>\*</sup> Your network must support 2.5Gbps Ethernet speeds over Cat5e or greater cabling.

# Kensington

### USB-C to 2.5G Ethernet Adapter

Part number: K38285WW | UPC code: 085896382850







# Connect to a wired network via USB-C

Connecting the USB-C (male) connector to your device's USB-C or Thunderbolt 3 port and the Ethernet cable to the RJ45 (female) port, will provide a secure hard-wired connection.

# Up to 2.5 times faster than current 1Gbps speeds

Provides a reliable connection and rapid data transfer speeds\*

# Increased productivity, decreased down time

Faster upload and download speeds, lower latency and better reliability than WiFi means less time waiting and more time doing





### **Bus-powered**

No power supply needed – simply connect it, and it works

### 2-year warranty

Rest assured knowing you're covered by Kensington

<sup>\*</sup> Your network must support 2.5Gbps Ethernet speeds over Cat5e or greater cabling.



# USB-C to 2.5G Ethernet Adapter

Part number: K38285WW | UPC code: 085896382850

c 1	
System	requirements
JyJtCIII	requirements

	Operating systems supported	Windows 7 or greater, macOS 10.6 or greater
Input/Output connector		
	Input	Type-C Male × 1
	Output	RJ45 Female × 1
RJ45 Basic specifications		
<u> </u>	Supported communication rate	10Mbps/100Mbps/1Gbps/2.5Gbps
	Main features supported	WOL(Wake-On-LAN) Full Duplex flow(10M/100M/1G/2.5G Rate) Auto-negotiation
Product dimensions		
	Product unit dimensions	Length: 2.93in / 74.5mm Width: 1.37in / 35mm Height: 0.61in / 15.5mm
	Weight	.07lbs / 34g
Environmental		
	Operating temperature	0°C to 40°C / 32°F to 104°F
	Operating humidity	10% to 85 % RH (no condensation)
	Storage temperature	-10°C to 70°C / 14°F to 158°F
	Storage humidity	5% to 90 % RH (no condensation)
Power consumption		
	Voltage	4.75V ~ 5.25V
	Standby power	<60mA (When Ethernet cable is not connected
	Normal operating power	<80mA 10Mbps <130mA 100Mbps <300mA 1Gbps <460mA 2.5Gbps
Country of origin, regulatory a	and warranty	
	Country of origin	Vietnam
	Certifications	FCC, CE
	Warranty year	2 years
Package		
	Package contents	Main unit x 1, User manual x 1
	Packaging dimension	131 x 102 x 24mm (5.16 x 4.01 x .94in)
	Packaging weight	0.085kg (3oz)





All specifications are subject to change without notice. Products may not be available in all markets. Kensington and the ACCO name and design are registered trademarks of ACCO Brands. Kensington The Professionals' Choice is a trademark of ACCO Brands. All other registered and unregistered trademarks are the property of their respective owners. © 2019 Kensington Computer Products Group, a division of ACCO Brands. All rights reserved. CBT27243EN